## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

ABANDON\*
Surface casing And Cement Record

Dec. 1973	Form Approved.  Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 27024
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas well d other	Mesa-Twin Mounds 9. WELL NO.
2. NAME OF OPERATOR	#1
Lobo Production	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Wildcat Gallup/ Basin Dakota
P.O. Box 2364 Farmington NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR
below.)	Sec. 30, T30N, R14W
AT SURFACE:790 FNL 990 FWL AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Dame AT TOTAL DEPTH: Same	San Juan NM
Danc	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	5492 GR
TEST WATER SHUT-OFF PRACTURE TREAT PRACTURE TREAT	
SHOOT OR ACIDIZE U JUN 3 0 1983	
PULL OR ALTER CASING [	the treatile of marche completion or zone y
MULTIPLE COMPLETE	RVEY JULIT OIV.
MULTIPLE COMPLETE  CHANGE ZONES  D. S. GEOLOGICAL SU FARMINGTON, N. L	w.
ABANDON* (other) Surface casing And Cement Record	RVEY OIL CON. DIV.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/27/83 Aztec Well Service moved on location.

Spud well @ 12:00 midnight. Drilled 124" hole to 215'KB 6/28/83 Ran 5 joints 8 5/8" 24# K55, ST & C, 8RD, R3 casing 200.90'. Landed @ 212.90' KB. Cemented with 150 sks (127.12 cuft.) class "B" with \pm4#/sk flocele and 3% CaCl2. Plug down at 9:45 am..Circulated cement to surface. WOC 12 hours. Test BOP to 600 psi.

DATE	6-28-83
e)	- Erren Gur Lagrad
DATE	JUL <b>07</b> 1983
	e)

"See Instructions on Reverse Side