Form approved.

LPASE DESIGNATION AND SECTION	
Expires August 31, 1085	

Form 3160-5 (November 1983) (Formerly 9-331)	DEPARTM	JNITED STAT IENT OF THE JOF LAND MAN	INTERIOR	SUBMIT IN TRIPLIC, (Other lustructions of verse side)	ATE Expir	et Bureau No. 100- es August 31, 108 ESIGNATION AND BEEL 764	5		
SUND (Do not use this fo	RY NOTI	CES AND RE	PORTS ON	WELLS to a different reservoir.	6. IF INDIA	N, ALLOTTEE OR TRIB	E NAMI		
OIL GAB WELL X					7. UNIT AGE	RECMENT NAME			
2. NAME OF OPERATOR					8. FARM OR Schuma	Chon			
	Paso N	atural Gas	Company		9. WELL NO				
3. ADDRESS OF OPERATOR PO	st Offi	ce Box 4289	,Farming	ton, N 67499	10A				
					Blanco Mesa Verde				
	•		REA	OG 26 1985 OF THE MANAGEMEN TO OF THE MESOURCE ASE MINISTON RESOURCE ASE THE OF Notice, Report,	11. SEC., T. Sec. 17 N.M.P.	. e., m., oe blk. and e ^{et} T ^{oe} 30 - N , R - M .	10-1		
14, PERMIT NO.		15. ELEVATIONS (Sho	w whether DF, RT, C	NOTON RESOURCE	12. COUNTY San Ju	or Parise 13. STA	TE		
16.	Check App	propriate Box To	Indicate Natur	e of Notice, Report,	or Other Data				
נסא	NOTICE OF INTENTION TO:				BHEQUENT REPORT	UBNT REPORT OF:			
TEST WATER SHUT-OFF	Pt	LL OR ALTER CASING		WATER SHUT-OFF		REPAIRING WELL			
FRACTURE TREAT		ULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CASING			
SHOOT OR ACIDIZE	^1	BANDON®		SHOOTING OR ACIDIZING	Running C	BANDONMENT*	_[
REPAIR WELL	CI	IANGE PLANS			suits of multiple of	completion on Well	_		
(Other) 17. DESCRIBE PROPUSED OR CO	OUBLETED OPER	TIONS (Clearly state	all pertinent det		completion Report : lates, including est		ing an		
proposed work. If w nent to this work.) *	ell is direction	ally drilled, give sub	surface locations	and measured and true v	ertical depths for	all markers and zone	s pert		
8-22-85	TD 327	2'. Ran	78 jts. 7	", 20.0#, K-5 ted with 200	55 interme	diate casi	ng, 5		
	3200°	ith 6% ael	2% calc	ium chloride	and $1/2$	u.ft./sack			
		~ (386 cm	ft) foll	nwed by 100 s	sks. Liass	S B WILL	<i>L l</i> o		
	calciu	m chloride	(118 cu.	ft.). WOC 12	2 hours.	Held 1200#	/30		
	min.	Top of cem	ent at 16	00' by T.S.					
8-25-85	TD 572	0'. Ran 6	3 jts. 4	1/2", 10.5#, collar set (J-55 casi	ng liner,			
	26071	set @ 5720	'. Float	collar set (@ 5712'.	Top of lin	er		
••	hangor	יצווג מ.	Camented	with 50 sks.	. Class t	5" 5U/5U PO	۷,		
	29 001	2 n d 1) h %	# 1 111 7	s annitive i	DZ. Lu.i L.	, and Loo s	KS.		
· · · · · · · ·	Class	"B" 50/50	Poz with	2% gel, 6.25	# 91150H10	.e, 1/4# F+ 1 WNC 1	8		
	flocel	e, and U.b	% fluid i	oss additive	(394 Cu.)	U., 1100 1	•		
	nours.	Circulat	eu iiner.			Bran.			
		• •			≈ () ∧		1		
		.*			O),	G28 785			
	•				Di	04/			

8-26-85 Drilling Clerk ACCEPTED FOR RECORD AUG 27 1985

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA