

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ X OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Meridian Oil Inc.		8. FARM OR LEASE NAME Grambling C
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499		9. WELL NO. 202
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1630'N, 1495'E		10. FIELD AND POOL, OR WILDCAT Undes. Fruitland Coal
14. PERMIT NO.		11. SEC. T. S. M. OR BLM. AND SURVEY OR AREA Sec. 14, T-30-N, R-10-W N.M.P.M.
15. ELEVATIONS (Show whether OF, BT, GR, etc.) 6403'GL		12. COUNTY OR PARISH San Juan
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

09-04-88 Spudded well at 2:00 pm 09-04-88. Drilled to 227'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 227'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (177 cu.ft.). Circulated to surface. WOC 12 hrs. Tested 600#/30 minutes. Held ok.

09-07-88 TD 2925'. Ran 67 jts. 7", 20.0#, K-55 intermediate casing, 2914' set @ 2926'. Cemented with 370 sks. Class "B" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (721 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Regulatory Affairs

DATE

09-06-88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side