

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499

4. Location of Well
1600'N, 1615'W

5. Lease Number
SF-078129

6. If Indian, All.or
Tribe Name

7. Unit Agreement Name

8. Farm or Lease Name
Pierce

9. Well No.
1R

10. Field, Pool, Wildcat
Blanco Mesa Verde

11. Sec. T. R. M. or Blk
Sec. 17, T-30-N, R-09-W
NMMPM

14. Permit No.

15. Elevations
6355' GR

12. County
San Juan

13. State
NM

16. Intent to/Subsequent Report of : Spud and Run Casing

17. Describe proposed or completed operations:

SPUD DATE: 11-12-89

SPUD TIME: 1630

TD 235' Ran 5 jts of 9 5/8", 40#, N-80 casing, 220' set @ 234'. Thread locked first jt. All 9 5/8" collars & shoe are spot welded to casing. Cmt'd w/150 sx Class "B" cement w/ 1/4# flocele/sx & 3% calcium chloride (177 cuft). Circulated 12 bbls to surface. Pressure tested to 200 psi.

11-17-89

TD 3396' Ran 83 jts of 7", 23#, K-55 casing, 3301' set @ 3395', guide shoe @ 3395', float collar @ 3355', casing packer top @ 2526', stage tool @ 2524'. Cmt'd 1st stage w/75 sx of Class "B" cmt 65/35 poz, 6% gel, 2% CaCl2, 0.5 cu ft perlite (119 cu ft.). Tail w/100 sx Class "B" cmt w/2% CaCl2 (118 cu ft.). Circ 5 bbls to surface. Cemented 2nd stage w/450 sx Class "B" 65/35 poz, 6% gel, 2% CaCl2, 0.5 cu ft perlite (715 cu ft.). Tail w/50 sx Class "B" cmt w/2% CaCl2 (59 cu ft.). Circulated 30 bbls to surface.

18. Authorized by: J. D. Tzeli
Regulatory Affairs

11/22/89
Date

NOTE: This format is issued in lieu of US BLM Form 3160-5

ACCEPTED FOR RECORD

(This space for Federal or State office use)

FEB 01 1990

APPROVED BY _____ TITLE _____
CONDITION OF APPROVAL, IF ANY:

DATE

FARMINGTON RESOURCE AREA

BY W. J.

WVOD