

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells - 5 11 1:21

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1815'FNL, 895'FEL, Sec.7, T-31-N, R-8-W, NMPM

5. Lease Number

SF-078510

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Oxnard #332

9. API Well No.

30-045-27656

10. Field and Pool

Basin Fruitland Coal

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☒ Notice of Intent

☐ Abandonment

☐ Change of Plans

☐ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - pump installation

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure and wellbore diagram.

ACCEPTED FOR RECORD

FEB 08 2000

FARMINGTON DISTRICT OFFICE

20 *K. H. M.*

14. I hereby certify that the foregoing is true and correct.

Signed *Peggy Cole* Title Regulatory Administrator Date 2/2/00
TLW

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

Oxnard #332
PUMPING UNIT INSTALLATION PROCEDURE
1/31/00


Unit H, Section 7, T31N-R8W, San Juan County, New Mexico

Lat. 36.914383 / 36° 54.86'
Long. 107.710129 / 107° 42.61'

1. MIRU pulling unit.
2. NDWH / NU BOP. Kill if necessary with produced Fruitland coal water. Note: Additional single BOP equipped for 3-1/2" ~~and~~ 2-7/8" tubulars is required.
3. PU one joint of tubing and TIH to tag for fill.
4. TOOH and lay down tubing (Tubing is set @ 3290'. There are 87 joints of 3-1/2" 9.3# J-55, 14 joints of 2-7/8", 6.5# J-55 and an "F" nipple @ 3256').
5. PU 4-3/4" bit and 2-3/8", 4.7#, J-55 EUE tubing and TIH to COTD. Circulate hole clean. (Note: COTD is @ ~3308'.)
6. TIH w/ 2-3/8" tubing string configured for downhole pump and land @ 3303'. Purge valve will be on bottom, followed by pup joint, perforated sub, and seating nipple. Space out as needed with pup joints.
7. Hang tubing in donut. ND BOP / NUWH.
8. TIH w/ new 1.25" top hold down pump, 3/4" Grade D sucker rods w/ spray metal couplings, polished rod, and polished rod liner. (Note: Vendor contact is listed below)
9. Seat the downhole pump, hang horses head, and space out pump.
10. Load tubing, and pressure test.
11. Start pumping unit and test (adjust spacing as required).
12. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.



Prepared: D.W. Mussett

 2-1-00
Approved: Drilling Supt.

Pump vendor: ENERGY PUMP
Leo Noyes @ 564-2874

Oxnard # 332
01/27/00
Basin Fruitland Coal
1815' FNL 895' FEL (Unit H), Section 7, T31N-R8W, San Juan Co., New Mexico

Completed: 12/7/1990



Workover History:
 12/1/95 Recavitated