UNITED STATES

DZPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	es and Reports on Wel	4° Ph 1: 22		
. Type of Well GAS			5.	Lease Number SF-080376 If Indian, All. or Tribe Name Unit Agreement Nam
. Name of Operator		NI 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		San Juan 32-9 Unit
RESOURCES OIL E	GAS COMPANY	₽₩ ************************************		
01 1 a	GAD COMPANI		8.	Well Name & Number
. Address & Phone No. of Operato				San Juan 32-9 U #2
PO Box 4289, Farmington, NM	87499 (505) 326-9700	_	9.	API Well No. 30-045-27961
. Location of Well, Footage, Sec	•		10.	Field and Pool
1290'FNL, 845'FEL, Sec.9, T-31	L-N, R-9-W, NMPM		11.	Basin Fruitland Co County and State San Juan Co, NM
12. CHECK APPROPRIATE BOX TO INDI	ICATE NATURE OF NOTICE	REPORT, O	THER	DATA
Type of Submission	Type of Ac			
X Notice of Intent		Change o		
0.1		New Cons		
Subsequent Report	Plugging Back _ Casing Repair	Non-Rout		Fracturing
Final Abandonment	Altering Casing _	Conversi		
	X Other - Pump Inst	allation		
3. Describe Proposed or Comple It is intended to install a procedure and wellbore diag	a pump in the subject	well accord	ing t	to the attached

San Juan 32-9 Unit #258 PUMPING UNIT INSTALLATION PROCEDURE 10/26/99

Unit A, Section 9, T31N, R9W, San Juan County, New Mexico Aircare Lat. 36 54.97' Aircare Long. 107 46.67'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU 1 JT. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3507', THERE ARE 112 JTS. OF 2-3/8" 4.7# J-55 WITH F-NIPPLE @ 3474').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 3512'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(3502'-3512'), 2-3/8"x6' PUP JOINT(3496'-3502'), 2-3/8"x4' PERFORATED SUB(3492'-3496') AND 2-3/8" SN @ 3492'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE 1-1/4" SINKER BARS, APPROX. 137 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2' ,4' ,6' ,8') TO SPACE OUT, ONE 1-1/4"x 22 3/4" PIN POLISHED ROD AND ONE 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles Office: 326-9584

Home: 325-8164 Pager: 324-2636 Approved: Drilling Supt.

Pump Vendor is Energy Pump & Supply @ 564-2874.

San Juan 32-9 Unit #258 10/22/99

Basin Fruitland Coal Unit A, Section 9, T31N, R9W, San Juan County, New Mexico

