

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells.

1. Type of Well GAS 2. Name of Operator MERIDIAN OIL 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 1763' FSL, 1134' FWL, Sec. 9, T-31-N, R-9-W, NMPM	5. Lease Number SF-080376 6. If Indian, All. or Tribe Name 7. Unit Agreement Name San Juan 32-9 Unit 8. Well Name & Number San Juan 32-9 U #107 9. API Well No. 30-045-28096 10. Field and Pool Blanco Pictured Cliffs 11. County and State San Juan Co, NM
---	--

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Remedial cementing

13. Describe Proposed or Completed Operations

4-5-95 MIRU. ND WH. NU BOP. TOO H w/113 jts tbg. RU, ran gauge ring. Set RBP @ 3400'. Spot sd on top of RBP. Load hole w/wtr. Attempt to PT plug. Circ through bradenhead. RD. TIH w/FB pkr. Found hole in 4 1/2" csg @ 1920-1951'. Close bypass on pkr. PT tbg to 1000 psi, OK. TOO H to 1700'. Set pkr. SDON.

4-6-95 Reset pkt @ 1700'. Pressure up backside to 500 psi. RU, establish injection. Pump 50 sx Class "B" neat cmt. Pump 190 sx 65/35 poz w/2% gel. Lost returns. Pump 80 sx Class "B" cmt w/0.3% Halad-344, 5% Cal-seal, 2% calcium chloride. Displace cmt to 120' below pkr. Final sqz pressure 1250 psi. WOC. Release pkr, TOO H. TIH, tag cmt @ 1840'. Drill cmt @ 1840-1892'. TOO H. SDON.

4-7-95 TIH, drill cmt @ 1892-1930'. Circ hole clean. PT csg to 1000 psi, OK. TOO H. RU, ran CBL @ 250-2425', TOC @ 260'. Perf 4 sqz holes @ 610'. RD. Circ through perfs and out bradenhead w/70 bbl wtr. RU, pump 125 sx Class "B" cmt w/0.3% Halad-344, 5% Cal-Seal. Start to displace w/1 /2 bbl wtr. Open bypass, reverse out 1 bbl cmt. Unseat pkr, TOO H. Pressure up csg to 500 psi. WOC. SDON.

4-8-95 TIH. Drill cmt @ 437-620'. Circ hole clean. TOO H. PT csg to 1000 psi, OK. RU, ran CBL @ 250-2425', TOC @ 270'. TIH w/csg scraper. CO sd on top of RBP. TOO H w/RBP. TIH w/57 jts 2 3/8" 4.7# J-55 tbg, landed @ 3579'. ND BOP. NU WH. SDON.

4-9-95 RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed *[Signature]* Title Regulatory Affairs

Date 4/10/95

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date APR 13 1995

CONDITION OF APPROVAL, if any:

FARMINGTON DISTRICT OFFICE