

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(See other instructions on reverse side)

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

SF-080376

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-9 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 32-9 Unit #112

9. API WELL NO.

30-045-28573

10. FIELD AND POOL, OR WILDCAT

Unders. Pictured Cliffs

11. SEC. T. R. M. OR BLOCK AND SURVEY OR AREA

Sec. 9, T-31-N, R-9-W
NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL:

OIL WELL ☐ GAS WELL ☒ DRY ☐ Other

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REVR. ☐ Other

2. NAME OF OPERATOR

Meridian Oil Inc.

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1010' FSL, 1115' FEL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

9-12-92

16. DATE T.D. REACHED

9-15-92

17. DATE COMPL. (Ready to prod.)

10-28-92

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6595' GL

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

3665'

21. PLUG. BACK T.D., MD & TVD

22. HOW MANY* COMPLEMENTS

HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

yes

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

Pictured Cliffs (3488-3570') DEC 21 1992

25. WAS DIRECTIONAL SURVEY MADE
no

26. TYPE ELECTRIC AND OTHER LOGS RUN

Ind/Dens/Neut/ML

OIL CON. DIST. 3

27. WAS WELL CORROD

no

29. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24.0#	226'	12 1/4"	220 cu.ft.	
4 1/2"	10.5#	3664'	7 7/8"	1781 cu.ft.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	3592'	

31. PREPARATION RECORD (Interval, size and number)

3488-91', 3494-3502', 3504-11',
3516-23', 3526-41', 3546-52',
3556-61', 3565-70'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3488-3570'	203,100# sand; foam, N2, gel

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
10-28-92		flowing-capable of comm.hydrocarbon prod.				shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF	WATER—BBL.	GAS-OIL RATIO
11-12-92	3 hrs	3/4"	→		2194	--	--
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
149	305	→	--	3313	--	--	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

to be sold

TEST WITNESSED BY

S. Stamets

ACCEPTED FOR RECORD

35. LIST OF ATTACHMENTS

none

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Regulatory Affairs

DATE

12-3-92

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2120'	2143'	White, cr-gr ss.			
Kirtland	2143'	3016'	Gry sh interbedded w/tight, gry, fine-gr ss.			
Fruitland	3016'	3476'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Ojo Alamo Kirtland Fruitland	2120' 2143' 3016'	
Pictured Cliffs	3476'	3665'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3476'	