

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals

**CONFIDENTIAL**

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
AMOCO PRODUCTION COMPANY

3. Address and Telephone No.  
P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Lotage, Sec., T., R., M., or Survey Description)

1070' FNL, 1025' FEL

Section 33 Township 31N Range 7W

Attention: D. Tallant

(303) 830-5427

5. Lease Designation and Serial No.

SF-079043

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

North East Blanco Unit #308

9. API Well No.

30-045-28985

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

Sanchuan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud & Set

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion of Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 17.5" surface hole on 9/18/93 at 5:30 hrs. Drilled to 398'

Set 13.375" 61# K-55 surface casing at 395'. Cemented with 560sx CLB. Circulated 45 BBLS to the surface.

Pressure tested casing to 1500 psi. Drilled a 12.25" hole to a depth of 3483' on 9/26/93. Set 9-5/8" 36# J-55 intermediate casing at 3742'. Cemented with 1st Sg - 315sx CLB, 2nd Sg - 660sx Light B, Tail w/ 100sx CLB. Circulated 83 BBLS to the surface. Pressure tested casing to 1500 psi.

Drilled a 8-3/4" hole to a depth of 7050' on 10/6/93. Set 7", 23#, J-55 protective casing at 6705'. Cemented with 450sx CLB, 250sx CLB. TOC @ 2750'.

Drilled a 6.25" hole to a TD depth of 8172' on 10/21/93. Set 4-1/2", 11.6#, N-80 Production Liner, Top at 6479', Bottom at 8172' cemented with 35sx CLG. TOC @ 6479'.

Rig released at 10:00 hrs. on 10/21/93.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Date

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Date

DEC 22 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

AMOCO

FARMINGTON DISTRICT OFFICE