| Subjust 3 Copies to Appropriate District Office | State of New M Energy, Minerals and Natural | | | Form C-103 Revised 1-1-89 |
|---|---|---|--------------------------------------|---|
| DISTRICT I P.O. Box 1980, Hobbe, NM 88240 | OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088 | | WELL API NO. 30-045-28993 | |
| DISTRICT II P.O. Drawer DD, Artesia, NM 88210 | | | 5. Indicate Type of L | STATE FEE X |
| DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 | | | 6. State Oil & Gas L | ease No. |
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | | | 7. Lease Name or Unit Agreement Name | |
| 1. Type of Well: OIL OAS WELL WELL | OTHER | | Moseley | |
| 2. Name of Operator | | | 8. Well No. | |
| Robert L. Bayless 3. Address of Operator | | | 9. Pool name or Wildcat | |
| | armington, NM 87499 | | Aztec Pictured Cliffs | |
| 4 Well Location | 470 Feet From The South | tine and 16 | 45 Feet From T | he West Line |
| NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: | Township 30N 10. Elevation (Show when 5788 G Appropriate Box to Indica NTENTION TO: PLUG AND ABANDON CHANGE PLANS | TE Nature of Notice, F SUI REMEDIAL WORK COMMENCE DRILLIN CASING TEST AND C OTHER: Spud (| SEQUENT RE IGOPNS. | Data EPORT OF: ALTERING CASING PLUG AND ABANDONMENT Thing report) |
| SIONATURE | as true and complete to the best of my knowled | gc med behafEngineer | | DATE12/29/93 TELEPHONE NO. 326-2659 |
| (This space for State Un) APPROVED BY | M. Bayless | SUPERVISOR | DISTRICT #3 | DEC 3 0 1993 |

CONDITIONS OF APPROVAL, IF ANY

Robert L. Bayless

Moseley #1

1470' FSL & 1645' FWL

Section 2-T30N-R12W

San Juan County, New Mexico

MORNING REPORTS

Received verbal approval to change 7 5/8" surface casing to 8 5/8" surface casing on 12/27/93 by telephone conversation with Frank Chavez.

12/28/93
Move in and rig up L & B Speedrill. Spud 12 1/4" hole at 12:30 pm, 12/27/93. Drill to 123 ft and circulate hole clean. Drop survey and trip out of hole. Survey was 1/4 degree at 123 ft. Run 6 jts (121.95 ft) of 8 5/8" 24# J-55 ST&C used casing and land at 122 ft GL. Rig up Cementers Inc and cement with 100 sx Class B with 2% CaCl. Pump cement until cement returned to surface then displace with 5 bbls of water, circulating 5 bbls of cement to pit. Plug down at 6:30 pm, 12/27/93. WOC and nipple up.