

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS	API # (assigned by OCD) 30-045-29508
	5. Lease Number See
	6. State Oil&Gas Lease #
2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY	7. Lease Name/Unit Name Hartman Com
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	8. Well No. 4A
4. Location of Well, Footage, Sec., T, R, M 1035' FNL, 1695' FWL, Sec. 26, T-30-N, R-11-W, NMPM, San Juan County	9. Pool Name or Wildcat Elanco Mesaverde
	10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Spud
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

2-22-98 MIRU. Spud well @ 2:00 a.m. 2-22-98. Drill to 245'. Circ hole clean. TOOH. TIH w/5 jts 9 5/8" 32.3# WC-40 ST&C csg, set @ 238'. Cmtd w/200 sx Class "G" neat cmt w/3% calcium chloride, 0.25 pps Flocele (236 cu.ft.). Circ 10 bbl cmt to surface. WOC. NU BOP. PT BOP & csg to 600 psi/30 min, OK.

2-23-98 Drill to intermediate TD @ 2610'. Circ hole clean. TOOH. TIH w/59 jts 7" 20# J-55 ST&C csg, set @ 2600'. Pump 20 bbl gelled wtr ahead. Cmtc w/159 sx Class "G" neat cmt w/3% sodium metasilicate, 0.25 pps Cellophane, 5 pps Kolite, 0.1% defoamer (409 cu.ft.). Tailed w/235 sx Class "G" 50/50 poz w/5 pps Kolite, 0.25 pps Cellophane, 0.1% defoamer, 2% calcium chloride, 0.4% fluid loss (298 cu.ft.).

2-24-98 Circ 23 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

RECEIVED
FEB 27 1998
OIL CONSERVATION
DIVISION

SIGNATURE *Deputy Bradfield* Regulatory Administrator February 25, 1998

no
(This space for State Use)

Approved by Original Signed by FRANK T. CHAVEZ Title SUPERVISOR DISTRICT #3 Date FEB 27 1998