

Submit 3 Copies
to Appropriate
District Offices

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

P.O. BOX 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.
30-045-29940

5. Indicate type of Lease
STATE FEE

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Uptegrove

1. Type of Well:
OIL WELL GAS WELL OTHER

RECEIVED
AUG 25 1999
OIL CON. DIV.
DIST. 3

2. Name of Operator
Horace F. McKay, Jr.

1R

3. Address of Operator
P. O. Box 14738 Albuquerque, NM 87191-4738

9. Pool name or Wildcat
Flora Vista Fruitland Sand/Aztec Pictured Cliffs

4. Well Location
Unit Letter J 1845' Feet From The South Line and 1845' Feet From The East Line
Sectio 2 Township 30N Range 12W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
5740' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: _____		OTHER: _____	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pressure tested BOP and surface casing to 600 psi for 30 min. Held OK.
Drilled 6 1/4" hole to 2240' KB. Ran 151 jts of 4 1/2", 10.50#, J-55 casing.
Casing landed at 2229' KB. PBD of 2184' KB. Cemented with 100 sx (206 cf) of Class B cement containing 2% Sodium Metasilicate and 1/4 #/sk cello flakes.
Tailed in with 100 sx (118 cf) of Class B cement containing 2% CaCl and 1/4 #/sk cello flakes. TOC at 1450' KB. Shut in WOC.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dana L. Delventhal TITLE Agent DATE 8/16/99
TYPE OR PRINT NAME DANA L. DELVENTHAL TELEPHONE NO. (505) 326-4125

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN DEPUTY OIL & GAS INSPECTOR, DIST. #3

AUG 25 1999

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: