Submit 3 Copies to Appropriate District Office	State of New M Energy, Minerals and Natur		Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs NM 88241-1980 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 8741	Santa Fe, NM	o St. 33318/27	WELL API NO. 30-045-30175 Indicate Type of Lease STATE FEE X 6 State Oil & Gas Lease No.
(DO NOT USE THIS FORM FOR I	PROPOSALS TO DRILL OR TO DEEP SERVOIR. USE "APPLICATION FOR PEC-101) FOR SUCH PROPOSALS.)	LLS 0187.3	Lease Name or Unit Agreement Name Stedje Gas Com
Name of Operator Cross Timbers Operating Com Address of Operator		7 401	8. Well No. #2R 9. Pool name or Wildcat Basin Fruitland Coal
Unit LetterA :1,0	Township 30N Rai	er DF, RKB, RT, GR, etc 5,476' Ground	NMPM San Juan County
	ITENTION TO:		SEQUENT REPORT OF:
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:	PLUG AND ABANDON CHANGE PLANS	REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CE OTHER:	
	OperationsClearly state all pertinent de	<u> </u>	dates, including estimated date of starting any propose
Cross Timbers Operating drilling report is enc		ing phase of the	above mentioned well. A copy of the
I hereby certify that the information above	is true and complete to the best of my knowle	edge and belief. E Drilling Engine	er DATE 5/31/00

TTTLE

TELEPHONE NO.

SET OIL & GAS INSPECTOR, DIST. JUN - 1 2000

CONDITIONS OF APPROVAL, IF ANY:

(This space for State Use)

TYPE OR PRINT NAME

APPROVED BY_

Stedje Gas Com #2R

5/19/00	MIRU Cable Tool rig. Spudded 12-1/4" to 10'.
5/21/00	Spudded through boulders to 35'.
5/22/00	Spuded through boulders to 75'.
5/23/00	Spudded through boulders to 90'. Drove 9-5/8" csg to 45'. RDMO Cable tool rig.
5/25/00	MIRU Wayne Smith Drlg Rig #1. Drld 8-3/4" hole to 225'.
5/26/00	Drld to 260'. Set 6 jts 7" csg to 257'. Cmt 7" csg with 100 sx (118 cuft) cl "B" cmt w/2% CaCl2 & 1/4#/sx celloflake (mixed at 15.6 ppg). Circ 7 bbls (33 cuft) cmt to surface. SD. WOC.
5/27/00	Installed BOP's. Pressure test BOP's to 250/1,000 psig. Held OK. Drlg ahead.
5/28/00	Drlg ahead.
5/29/00	Reached TD at 1,834' KB. RIH w/open hole logs. Set 44 jts 4-1/2" csg @ 1,834' KB.
5/30/00	Cmt'd csg with 225 sx (465 cuft) Premium Lite LS cmt (65% Type III cmt, 35% poz, 6% gel, 10#/sx CSE) w/2% CaCl2 & 1/4#/sx Celloflake (12.5 ppg 2.07 cuft/sx). Circ 15 bbl (84 cuft) cmt to surface. Bumped Plug. Check float. Float held OK. Pressure Tested csg to1,100 psig. Held OK. ND BOP's. Set slips. Released Rig @ 9:00 a.m.