

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

REVISED

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT..." for such proposals

**SUBMIT IN TRIPLICATE****1. Type of Well**☐

Oil Well

☒

Gas Well

☐

Other

**2. Name of Operator**

Richardson Operating Company

**3. Address and Telephone No.**

1700 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000

**4. Location of Well (Footage, T, R, M, or Survey Description)**

1070' FSL &amp; 1454' FWL

Sec. 33-T30N-R14W

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

**5. Lease Designation and Serial No.**

NMSF-079968

**6. If Indian, Allottee or Tribe Name****7. If Unit or CA, Agreement Designation****8. Well Name and No.**

WF Federal 33-3

**9. API Well No.**

30-045-30378

**10. Field and Pool, or Exploratory Area**

Twin Mounds PC

**11. County or Parish, State**

San Juan County, NM

**12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA****TYPE OF SUBMISSION****TYPE OF ACTION**☐

Notice of Intent

☒

Subsequent Report

☐

Final Abandonment Notice

☐

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☐

Surface Casing/Cementing

☒

Other: see below

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note: Report results of multiple completion on Well

Completion or Recombination Report and Log form).

**13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.**

If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)\*

1-2-01 Spud 8 3/4" surface hole. Drill to 135'. Ran 3 jts 7" 20# casing to 133.5'. Cemented with 50 sx Class H with 1/4# celloflake per sx and 4% CaCl2. Circulated 3 bbls cement to surface.

1-3-01 Test BOP to 2000#. Drill cement and 6 1/4" hole to 950'.

1-4-01 Drill to 1060' GL (1065' KB) TD. Ran 28 jts 4 1/2" 10.5# casing to 1060'. Cemented with 65 sx Class H Neat w/ 2% S.M. and 85 sx Class H Neat with 1/4# celloflake per sx. Circulated 5 bbls cement to surface. Test casing to 2000#. PBD 1023' GL (1028' KB).

**14. I hereby certify that the foregoing is true and correct**Signed: Cathleen Colly

Title: Land Manager

Date: Mar 19 2001

(This space for Federal or State office use)


Approved by: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



✓  
X