

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____ 47/2 10

Lease No. 291191

Unit 9 A

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

San Juan 33-17-1955
 Well No. 1-25 is located 110 ft. from {N
 S} line and 910 ft. from {E
 W} line of sec. 25 on
 Section 25
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
 Project 25
 (Field) (County or Subdivision) (State or Territory)
 RECEIVED 24 1955

The elevation of the derrick floor above sea level is 24 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

12/1/59. After drilling to 3,370 feet with rotary rig, set 1 1/2 joints (2,350 ft) of 7-5/8" 26,000 lb 4-5" casing at 3,370 feet with 250 sacks of cement set with 2 1/2" 51 lbs per sack. On 11/7/59 pressure held without drop, so drilled cement and continued drilling with gas. After drilling to 5,336 feet, set 2,533 feet of (12/9/59 5-1/2" 17,000 lb 4-5" casing liner at 4,125 feet to top at 3,166 feet. Cemented with 350 sacks cement, 50/50 ozonix, 60 gal, 1 1/4 floccs per sack. On 12/11/59 squeezed top of liner with cool water. Used 100 sacks regular cement, 1000 pressure. On 12/12/59 pressure held a.k. Cleared out to 1803 ft. Perforated 2 slots per foot: 5717-5719; 5735-5737; 5755-5757; 5765-5767. Sand water fraced with 1,000 sand and 10,000 gal. water. On 12/13/59 pressure held at 1700 ft. 2000. Injection 84.5 barrels per minute. No ped 140 balls. Flushed with 4,240 barrels water.

"fracturing" of other work covered by separate report.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company W. H. & C. Co. Inc.

Address Box 72

Warrior to Law School

By [Signature]

Title Wagon Trail, Mount Washington