

(SUBMIT IN TRIPLICATE)

Land Office

075011

Lease No.

San Juan 32-5

Unit

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	XXXX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	XXXX
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 7, 1961

San Juan 32-5 Unit

Well No. 3-26 is located 500 ft. from N line and 2,450 ft. from W line of sec. 26  
NW/4 Section 26 32-N 6-W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Basin Dakota Rio Arriba County New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6,395 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

May 22, 1961. After drilling to 6110' RKB, set 253 joints of 4-1/2" H-80, 11.6#/LTD Casing - landed at 8,098.23' - with DV Tool at 5,916.45'. Cemented 1st stage with 300 sacks 50-50 Poz Mix with 4 1/2 gal. Displaced top plug and bumped float with 1700 psi. Released pressure, and float held. Had complete returns at 2:15 A.M. on May 22, 1961. Cemented 2nd stage with 200 sacks 5 1/2 gal. Displaced top plug with 52 BW. Closed DV tool with 2000 psi. Got no backflow. Had complete return at 6:55 A.M.

May 27, 1961 Completion Rig drilled stage collar and cleaned out to FBHD of 8050'. Tested casing to 5100 psi. Spotted 500 gal BDA on bottom. Perforated with 4 jet shots per foot using 3-1/8" Super dynamjet charges: 8028'-8029'; 7950'-7997'; 7937'-7940'; 7900'-7908'. Sand fractured with 43,000 gal. water 1 1/2 Calcium Chloride and 3 1/2 J-101/gal and 43,000# 20-40 sand. Dropped 75 balls. Avg. injection 39 BPM at 3700 psi.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company La Plata Gathering System, Inc.Address Box 726Farmington, New Mexico

By

C. Beeson Noel, Agent in Farmington

Title