

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

5. Lease Designation and Serial No.

NM 4462

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

SCHALK 62 #3

9. API Well No.

10. Field and Pool, or Exploratory Area

Blanco Pictured Cliffs East

11. County or Parish, State

Rio Arriba County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☐ Abandonment

☒ Recompletion

☒ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-17-94: Set cement retainer (4.5") @ 5276'; squeeze Mesa Verde formation from 5438' to 5689' with 39 sacks Class B cement; sting out of retainer and left 75' cement over retainer. Pressure test casing; run GSL log from 2800 to 4000'.

6-18-94: Run cement bond log from 3450' to 2520'.

6-21-94: Perforate (3351' to 3362') 2 shots/foot; 22 .375 holes; perforate (3366' to 3370') 2 shots/foot; 8 .375 holes; breakdown with 250 gallons 7-1/2% HCL; fracture well with 164 barrels 30 lb. gelled water, 50,000 lbs 20/40 sand and 287,000 SCF N2.

6-21-94: Flow well back.

6-23-94: Set bridge plug @ 3217'; perforate (3088' to 3098') 2 shots/foot; 20 .375 holes; perforate (3104' to 3118') 2 shots/foot; 28 .375 holes; perforate (3120 to 3122') 2 shots/foot; 4 .375 holes; perforate (3128' to 3133') 2 shots/foot; 10 .375 holes; breakdown with 250 gallons 7-1/2% HCL; fracture with 229 barrels 30 lb. gelled water, 21,700 lbs. 20/40 sand and 456,000 SCF N2.

6-24-94: Go in hole with 2-3/8" tubing and packer; set packer @ 2845'; swab well in and shut in.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title General Manager

Date 6/30/94

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any: [Signature]

Title _____

Date _____

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMOOD

FARMINGTON DISTRICT OFFICE

BY [Signature]