

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Northwest Pipeline Corporation
3. ADDRESS OF OPERATOR  
P.O. Box 90, Farmington, N.M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1630 FNL & 970 FEL  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other) Intermediate csg set

5. LEASE  
SF 078772
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Rosa Unit
8. FARM OR LEASE NAME  
Rosa Unit
9. WELL NO.  
#91
10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 35, T32N, R6W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
N.M.
14. API NO.  
30-039-22780
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-21-81 to 7-27-81 Drlg ahead to a depth of 3990'.

7-28-81 Ran 7", 20#, K-55, ST&C CF&I seamless csg & set @ 3990'. Float @ 3946.5'. National cmt'ed w/ 135 sx C1 "B" w/ 65/35 poz w/ 12% gel. Tailed w/ 75 sx C1 "B" w/ 2% CaCl<sub>2</sub>. Displaced plug w/ 155 bbls wtr & down @ 2030 hrs. Did not circulate cmt behind 7" csg. Calculated top of cmt @ 2392'.

7-29-81 Waiting on cement and drlg ahead to a depth of 5300'.

7-30-81 to 7-31-81 Drlg ahead.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE 7-31-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

djb/

\*See Instructions on Reverse Side

NMOCC

FARMINGTON, N.M.  
BY SM