

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 28277

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

ARBOLES 29 A #1

9. API Well No.

30-039-23272

10. Field and Pool, or Exploratory Area

BASIN FRUITLAND COAL

11. County or Parish, State

RIO ARRIBA COUNTY, NM

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil ☒ Gas ☐ Other
☐ Well ☒ Well

2. Name of Operator

VASTAR RESOURCES, INC.

3. Address and Telephone No.

1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1525' FSL, 1540' FWL, Section 29, T32N, R4W

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Plug sidetrack & redrill

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

It is proposed to plugback existing sidetrack and drill a new Fruitland Coal sidetrack as follows:

1. Run multislot survey across whipstock and window to determine sidetrack direction.
2. Spot 50 ex cement plug from PBTD (4175') to 4030' and 25 ex cement plug at window from 3831'-3750'. WOC & tag.
3. Pick up whipstock and run in hole to 3750' and orient 90 degrees from original sidetrack.
4. Mill window in 5-1/2" casing.
5. Drill 4-3/4" Fruitland Coal sidetrack to TD of 4175' (100' below bottom of coal for rat hole).
6. Underream open hole to 6" diameter.
7. Run 4" 11.00# L80 HY511 Flush Joint casing to TD.
8. Cement back to surface with the following:
Lead: 150 ex (300 cu ft) of 35:65 class B poz with 8% gel + 5#/ex Gilsenite + 1/4#/ex CF
Tail: 100 ex (138 cu ft) of 50:50 class B poz with 2% gel + 5#/ex Gilsenite + 1/4#/ex CF + 0.4% FLA
7. Log, perforate, breakdown, frac, run production tubing, and flow test Fruitland Coal.

Note: Verbal approval for the above granted by Jim Lavato on 9-12-00

cc: BLM, Farmington (Or + 3)

N. Hall

Well File

14. I hereby certify that the foregoing is true and correct

Signed W. Hughes

Title ENGINEER 505 599 4308

Date 9-12-00

(This space for Federal or State official use)
Approved by Jim Lovato

Title _____

Date SEP 18 2000

Conditions of approval, if any: