

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

VASTAR RESOURCES, INC.

3. Address and Telephone No.

1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1525' FSL, 1540' FWL, Section 29, T32N, R4W

5. Lease Designation and Serial No.

NM 28277

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

ARBOLES 29 A #1

9. API Well No.

30-039-23272

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

RIO ARRIBA COUNTY, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION



Notice of Intent



Subsequent Report



Final Abandonment Notice



Abandonment



Recompletion



Plugging Back



Casing Repair



Altering Casing



Other **Option to Sidetrack**



Change of Plans



New Construction



Non-Routine Fracturing



Water Shut-Off



Conversion to Injection



Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

As a supplement to the Re-entry APD approved July 10, 2000 the following option to Sidetrack is proposed:

1. Drill out cement plug from 3280' to 3800' (18' above cement retainer at 3818', 6' above 5-1/2" collar) and test casing.
2. Set whipstock at 3800' and mill window in 5-1/2" casing.
3. Drill 4-3/4" Fruitland Coal sidetrack to TD of 4175' (100' below bottom of coal for rathole).
4. Underream open hole to 8" diameter.
5. Run 4" 11.60# L80 HY511 Flush Joint casing to TD.
6. Cement back to surface with the following:
Lead: 150 sx (300 cu ft) of 35:65 class B poz with 6% gel + 5#/sx Gilsonite + 1/4#/sx CF
Tail: 100 sx (138 cu ft) of 50:50 class B poz with 2% gel + 5#/sx Gilsonite + 1/4#/sx CF + 0.4% FLA
7. Log, perforate, breakdown, frac, run production tubing, and flow test Fruitland Coal.

cc: BLM, Farmington (Dr + 3)

N. Hall

Well File

14. I hereby certify that the foregoing is true and correct

Signed

Charles W. Kugler

Title **ENGINEER 505 599 4308**

Date **7-28-00**

(This space for Federal or State office use)

Approved by

JL

Title

Date

8-2-00

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMOC

directional Survey
if side tracked ✓