

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 100
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 30016
2. NAME OF OPERATOR NASSAU RESOURCES, INC.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 809, Farmington, N.M. 87499		7. UNIT AGREEMENT NAME Carracas Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' FNL - 990' FEL		8. FARM OR LEASE NAME Carracas Unit 27 A
14. PERMIT NO.		9. WELL NO. #82
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 7164' GL; 7176' KB		10. FIELD AND POOL, OR WILDCAT WC Entrada
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T32N, R5W, NMPM
		12. COUNTY OR PARISH Rio Arriba
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud, surface csg. & test

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17-1/2" hole at 4:15 p.m. on 12/1/88.
Drilled to 322' and ran 10 jts. of 13-3/8", 54.4#/ft, K-55, ST&C, 8 Rd. casing.
Set at 319' KB with float collar at 292' KB.
Cemented with 385 sk Class "B" w/2% CaCl (454 cu.ft.)
Plug down at 5:40 p.m. on 12/2/88.
Full returns w/20 bbls. cement circulated to surface.
Pressure tested casing to 500 PSI for 30 minutes. Test good.

RECEIVED
MAIL ROOM

68 DEC -6 AM 11:30

FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED

James S. Hazen

TITLE

Field Supt.

DATE

12/5/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side