

1 DE 1 File
**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | |
|--|--|---|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> | | 5. LEASE DESIGNATION AND SERIAL NO. NM 29343 |
| 2. NAME OF OPERATOR NASSAU RESOURCES, INC. | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR P.O. BOX 809, Farmington, N.M. 87499 | | 7. UNIT AGREEMENT NAME Carracas Unit |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 970' FSL - 1580' FWL | | 8. FARM OR LEASE NAME Carracas Unit 27 A |
| 14. PERMIT NO. | | 9. WELL NO. #14 |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6841' GL; | | 10. FIELD AND POOL, OR WILDCAT WC Fruitland |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T32N, R5W, NMPM |
| | | 12. COUNTY OR PARISH Rio Arriba |
| | | 13. STATE N.M. |

13.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Spud, surface csg., test ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. **FOR NEW, PROPOSED OR COMPLETED OPERATIONS** (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MI & RU Four Corners Rig #7.
Spudded 12-1/4" hole at 8:30 p.m., 9-26-88.
Drilled to 377' & ran 8 jts. of 9-5/8", 36#, J-55 csg. (357.06').
Set at 369' KB.
Cemented with 190 sx Class "B" with 2% CaCl (224 cu.ft.).
Circulated to surface.
Plug down at 3:15 a.m. on 9-27-88.
Pressure tested at 1300 psi for 1-1/2 hours. Held okay.

RECEIVED

OCT 05 1988

OIL CON. DIV
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

James S. Hazen

TITLE Field Supt.

DATE 9-27-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

OCT 03 1988

FARMINGTON RESOURCE AREA

BY K/H