

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>	7. UNIT AGREEMENT NAME San Juan 32-5 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME San Juan 32-5 Unit
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	9. WELL NO. 107
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2045'N, 645'E	10. FIELD AND POOL, OR WILDCAT Undes. Fruitland Co.
11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA Sec. 26, T-32-N, R-06-N.M.P.M.	12. COUNTY OR PARISH 13. STATE Rio Arriba NM
14. PERMIT NO.	15. ELEVATIONS (Show whether OF, BT, GR, etc.) 6353' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Spud Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.*

CORRECTED COPY

10-31-88 Spudded well at 7:00 pm 10-31-88. Drilled to 229'. Ran 5 jts. 9 5/8", 32.3#, H-40 surface casing set at 229'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (177 cu.ft.). circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.

11-04-88 TD 2994'. Ran 68 jts. 7", 20.0#, K-55 intermediate casing, 2981' set @ 2994'. Cemented with 500 sx. Class "B" 65/35 Poz with 6% gel, 2% calcium chloride and 0.5% perlite/sx. (965 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min. Circ. 12 bbls. to surface.

RECEIVED

APR 25 1989

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Regulatory Affairs

DATE

11-07-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: