Ferm 3160--5 (November 1983) (Formerly 9-331)

NAS

P.0

580

14. PERS

## **UNITED STATES** DEPARTMENT OF THE INTERIOR (Other lastructions on re-

SUBMIT IN TRIPLICATE.

Budget Barcau l	No.	1004	
Expires August	31.	1985	
LEASE DESIGNATION	150	HERIAL.	

Rio Arriba

BUREAU OF LAND MANAGEMENT	NM 30015
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different caservoir.  Use "APPLICATION FOR PERMIT" for such proposals.	6 IF INDIAN, ALLOTTEE OR TRIBE HAME
CAS (T)	7. UNIT AGREEMENT NAME
WELL NOTHER SOMEY -2 14 6: 23	Carracas Unit 8. FARM OR LEAST NAME
SAU RESOURCES, INC.  TARMINGTON RESOURCE AREA FARMINGTON NEW MEXICO	Carracas Unit 18 B
Box 809, Farmington, N.M. 87499 THOS OF WELL (Report location clearly and in accordance with any State requirements.* also space 17 below.)	#15 10. FIELD AND POOL OF WILDCAT Basin Fruitland Coal
' FSL - 1710' FEL	11. SBC, T., B., M., OR BLE. AND SURVEY OR AREA
15 ELEVATIONS (Show whether DF, BT, GR, etc.)	Sec. 18, T32N, R4W

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:			
TEST WATER SHUT OFF	PULL OR ALT	PER CASING .	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT	MULTIPLE C	OMPLETE	FRACTUBE THEATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	AHANDON MENT*	
REPAIR WELL	CHANGE PLA	NS.	(Other) Spud, surface	csg. & test	X
(Other)			(NOTE: Report results of m	nultipie completion on Well	i '

17. DESCRIBE PROPOSED OR COMPLETED OFERATIONS (Clearly State all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.).

Spudded 12-1/4" hole at 9:15 pm, 4/28/89. Ran 336' of 9-5/8", 36#, J-55 csg. Set at 349' KB. Cemented with 55 sk of 65/35 w/ 2% CaCl and 1/4#/sk celoflake 50 sk Class "B" w/ 2% CaCl (169 cu.ft.). Plug down at 1:00 pm on 4/29/89. Circulated 5 bbls. of cement to surface. Pressure tested to 800# for 30 minutes. Test good.



	*See Instructions on Reverse Side	RY KLY
CONDITIONS OF APPROVAL, IF ANY:	MMOCG	MAY 02 1989
APPROVED BY	TITLE	
(This space for Federal or State office use)		ACCEPTED FOR RECORD
SIGNED Fran Perrin	TITLE Admin. Asst.	DATE _5/1/89