UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0175

Expires: March 31, 1993

Lease Designation and Serial No.

	NM 30015
SUNDRY NOTICES AND REPORTS ON WELLS	6. If Indian, Allottee or Tribe Name
Do not use this form for proposals to drill or deepen or reentry to a different reservoir.	: 03
Use "APPLICATION FOR PERMIT" for such proposats	
SUBMIT IN TRIPLICATE	7: If Unit or CA, Agreement Designation
SUBMIT IN TRIFLICATE (1997)	CARRAÇAS UNIT
Type of Well	CARRACAS UNIT
Oil Gas Well Other	8. Well Name and No.
. Name of Operator	CARRACAS 18 B # 15
VASTAR RESOURCES, INC.	9. API Well No.
Address and Telephone No.	30-039-24330
1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300	→
Location of Well (Footage, Sec., T., R., M., or Survey Description)	BASIN FRUITLAND COAL 11. County or Parish, State
	RIO ARRIBA, N.M.
SWSE 580 ' FSL & 1110 ' FEL SEC. 18, T-32N, R-4W	
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER	DATA
TYPE OF SUBMISSION	
Notice of Intent Abandonment	Change of Plans
Recompletion	New Construction
Subsequent Report Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off Conversion to Injection
Final Abandonment Notice Altering Casing Other RE PERF & RE FRAC	Dispose Water
Other NEFERI & REFERI	(Note: Report results of multiple completion on Well
	Completion or Recompletion Report and Log form.)
Vastar elected to reperforate and refrac the Fruitland Coal in the subject well in flow rates. Reperforated Fruitland Coal fm 4070' to 4094', and 4109'-4111', Total 20	an attempt to increase gas
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produc 04/11/2000 and were completed on 04/27/2000.	6' w/ 4 spf adding 104 noies 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produc 04/11/2000 and were completed on 04/27/2000.	6' w/ 4 spt adding 104 noies 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produc 04/11/2000 and were completed on 04/27/2000. cc: BLM, FMTN (Or+3)	6' w/ 4 spt adding 104 noies 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produc 04/11/2000 and were completed on 04/27/2000. cc: BLM, FMTN (Or+3) Hall Well File	6' w/ 4 spt adding 104 noies 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produc 04/11/2000 and were completed on 04/27/2000. cc: BLM. FMTN (Or+3) No. Hall	6' w/ 4 spf adding 104 noies 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produce 04/11/2000 and were completed on 04/27/2000. cc: BLM. FMTN (Or + 3) Note that the loregoing is true and correct with the loregoing is true and t	6' w/ 4 spt adding 104 holes 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produce 04/11/2000 and were completed on 04/27/2000. cc. BLM, FMTN (Or + 3) N, Hall Well File 14, Thereby certify that the foregoing sertile and correct Signed Title WORKOVER SUPERVISOR	6' w/ 4 spt adding 104 holes 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produce 04/11/2000 and were completed on 04/27/2000. CC: BLM. FMTN (Or + 3) Hall Well File Workover supervisor Workover Supervisor Title Workover Supervisor	5' w/ 4 spt adding 104 holes 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on Date
w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 72 gel w/ sandwedge containing 1445 sx 20/40 Brady sand. After cleaning out the 5 1.9", 2.76#, J-55, 10Rd IJ tbg assembly was run w/ a profile nipple and WL re-e 4052'. Flowed and cleaned well to a flowback tank and returned the well to produc 04/11/2000 and were completed on 04/27/2000. CC: BLM. FMTN (Or + 3) Hall Well File 14, Thereby certify that the foregoing is fride and correct Title WORKOVER SUPERVISOR Title Conditions of approval, if any:	6' w/ 4 spt adding 104 holes 2460 gal 25 # Delta frac 140 1/2" csg to 4180', (PBTD), a ntry guide. No pkr, EOT at tion. Operations started on

*See Instruction on Reverse Side

or representations as to any matter within its jurisdiction.

Smn_ urrice