UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

		NM 59704
	ES AND REPORTS ON WELLS	If Indian, Allottee or Tribe Name
	o drill or deepen or reentry to a different reservoir.	
Use "APPLICATION	I FOR PERMIT" for such proposals	
SUBMIT IN	TRIPLICATE	7. If Unit or CA, Agreement Designation
Type of Well	<u> </u>	CARRACAS UNIT
Oil Gas	TINE STORY	
Well Other		8. Well Name and No.
Name of Operator		CARRACAS 26 A # 2
ASTAR RESOURCES, INC.	- Ro Ro 2003	9. API Well No.
Address and Telephone No.	97404 (505) 500 4306	30-039-24402 10. Field and Pool, or Exploratory Area
16 E. MOJAVE ST., FARMINGTON, NM	57401 (303) 399-430 9	BASIN FRUITLAND COAL
ocation of Well (Footage, Sec., T., R., M., or Survey Description)		11. County or Parish, State
R		
VNE 790' FNL & 1450' FEL SEC. 26, T-3	ON DEW	DIO ADDIDA NM
		RIO ARRIBA, NM
. CHECK APPROPRIATE BOX(s) TO I	NDICATE NATURE OF NOTICE, REPORT, OR OTHER	DATA
TYPE OF SUBMISSION		
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
, ,	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other RE-PERF & RE-FRAC	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Vastar elected to reperforate and flow rates. Reperforated Fruitland	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h	an attempt to increase gas oles w/ 0.42" diameter and
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' (2 GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after cle	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed with the completed wit	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' (2 GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after cle	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed to the completed with the completed of t	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' (2 GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after cle	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed on 08/01/2000 is true and correct gned whis space for Federal or State office beet.	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' 62 GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after clean on 08/16/2000.	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and ean up. Operations started
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed to the complete description of the complete	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' & GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after cle on 08/16/2000.	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and ean up. Operations started
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed on 08/01/2000 and were completed in the reperformed was a space for Federal or State office been proved by	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' 62 GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after clean on 08/16/2000.	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and ean up. Operations started
Vastar elected to reperforate and flow rates. Reperforated Fruitland treated all perfs w/ 500 gal 10 % containing 1,000 sx 20/40 Brady s 10RD IJ tbg assembly was run w/ 2 clean well to a flowback tank. Op on 08/01/2000 and were completed to the completed with the completed of t	I refrac the Fruitland Coal in the subject well in d Coal fm 3872-3896 24' w/ 4 spf adding 96 h formic acid followed w/ 34,960 gal 25# Delta and. After cleaning out the 5 1/2" csg to 3987' 62 GLM'S, 'F' nipple and WL re-entry guide. No perator will return the well to production after clean on 08/16/2000.	an attempt to increase gas oles w/ 0.42" diameter and frac 140 gel w/ sandwedge (PBTD), a 1.9", 2.76#, J-55, okr, EOT at 3866'. Flow and ean up. Operations started

sun - mi

Mr. L.