or representations as to any matter within its jurisdiction.

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

March 31, 1993

5. Lease Designation and Senal No.

NM 305885 6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals		
SUBMIT IN TRI	PLICATE NO 13 14/52	7. If Unit or CA, Agreement Designation
Type of Well Oil Gas		CARRACAS UNIT
Well Well Other	AUG 2000	8. Well Name and No.
2. Name of Operator	RECEIVED 3	CARRACAS FR 108
VASTAR RESOURCES, INC.	S RECEIVED 2	9. API Well No.
Address and Telephone No.	OIL CON. DIV	30-039-24653
1816 E. MOJAVE ST., FARMINGTON, NM 8740	01 (505) 599-4300 COST. 3	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	(1)	BASIN FRUITLAND COAL
	A/C00,000113	11. County or Parish, State
	62.85	
SWSW 840' FSL & 1190' FWL SEC. 24, T-32N,	R-4W	RIO ARRIBA, NM
12. CHECK APPROPRIATE BOX(s) TO INDI	CATE NATURE OF NOTICE, REPORT, OR OTHER	DATA
TYPE OF SUBMISSION		
Notice of Intent	Abandonment	Change of Plans
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
_		=
	Recompletion	New Construction
_	Recompletion Plugging Back	New Construction Non-Routine Fracturing
Subsequent Report	Recompletion Plugging Back Casing Repair Altering Casing	New Construction Non-Routine Fracturing Water Shut-Off
Subsequent Report	Recompletion Plugging Back Casing Repair Altering Casing	New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection
Subsequent Report	Recompletion Plugging Back Casing Repair Altering Casing	New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water

Vastar elected to reperforate and refrac the Fruitland Coals in the subject well in an attempt to increase gas flow rates. Reperforated Fruitland Coal fm 3742-45 (3'), 3764-80, (16') and 3796-3800, (4'), 23' w/ 4 spf adding 92 holes w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 56,916 gal 25# Delta frac 140 gel w/ sandwedge containing 930 sx 20/40 Brady sand. After cleaning out the 5 1/2" csg to 3908' (PBTD), a 1.9", 2.76#, J-55, 10RD IJ tbg assembly was run w/ 2 GLM'S, profile nipple and WL Re-entry guide . No pkr, EOT at 3720'. Flowed and cleaned well to a flowback tank and prepare to return to production. Operations started on 07/07/2000 and were completed on 07/22/2000.

cc: BLM, Farmington (Or + 3)		
N. Hall WellPile		
14. Thereby cartify that the foregoing is true and correct		
Signed & m Wanger	Title WORKOVER SUPERVISOR	Date07/27/2000
(This space for Federal or State office use)		
Approved by	Title	Date
Conditions of approval, if any:		
		SFOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

*See Instruction on Reverse Side

^{13.} Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*