UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Eureau No. 1004-0135
Expires: March 31, 1993

Lease Designation and Senal No.

NM 3058# 5

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I Type of Well CARRACAS UNIT Oil Gas ☐ Well Well Other Well Name and No. 2. Name of Operator **CARRACAS FR 108** VASTAR RESOURCES, INC. 9. API Well No. 3. Address and Telephone No 30-039-24653 10. Field and Pool, or Exploratory Area 1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300 **BASIN FRUITLAND COAL** 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State SWSW 840' FSL & 1190' FWL SEC. 24, T-32N, R-4W RIO ARRIBA, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion New Construction \boxtimes Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection RE-PERE & RE-FRAC Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Vastar elected to reperforate and refrac the Fruitland Coals in the subject well in an attempt to increase gas flow rates. Reperforated Fruitland Coal fm 3742-45 (3'), 3764-80, (16') and 3796-3800, (4'),23' w/ 4 spf adding 92 holes w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 56,916 gal 25# Delta frac 140 gel w/ sandwedge containing 930 sx 20/40 Brady sand. After cleaning out the 5 1/2" csg to 3908' (PBTD), a 1.9", 2.76#, J-55, 10RD IJ tbg assembly was run w/ 2 GLM'S, profile nipple and WL Re-entry guide. No pkr, EOT at 3720'. Flowed and cleaned well to a flowback tank and prepare to return to production. Operations started on 07/07/2000 and were completed on 07/22/2000.

cc: BLM, Farmington (Or + 3)

N.(Hall Well Fil

14. I hereby sertify that the foregoing is true and correct

Signed X m Margon

Title WORKOVER SUPERVISOR

07/27/2000

(This space for Federal or State office use)

Approved by_____

Date____

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any fals ACCEPTEGETER FCORL or representations as to any matter within its jurisdiction.

See Instruction on Reverse Side

4UC 1 5 2000

NMOCD

EMM - TICE