

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

FORM APPROVED

OMB NO. 1004-0137

Expires: February 28, 1995

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL ☐ GAS ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW ☒ WORK ☐ DEEP- ☐ PLUG ☐ DIFF. ☐ Other ☐

2. NAME OF OPERATOR
Taurus Exploration U.S.A., Inc.

3. ADDRESS AND TELEPHONE NO.
2198 Bloomfield Highway; Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*
At surface
627' FSL, 1517' FWL
At top prod. interval reported below

At total depth

14. PERMIT NO. DATE ISSUED
12. COUNTY OR PARISH RIO ARriba 13. STATE NM

15. DATE SPUDDED 7/5/98 16. DATE T.D. REACHED 7/17/98 17. DATE COMPL. (Ready to prod.) 10/13/98 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6377' GR 19. ELEV. CASINGHEAD 6377'

20. TOTAL DEPTH, MD & TVD 8092' 21. PLUG, BACK T.D., MD & TVD 8070' 22. IF MULTIPLE COMPL., HOW MANY* 2 23. INTERVALS DRILLED BY 0-8092 ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*
7929-8010' Dakota, 4396-5918' Mesa Verde DHC on 1 Comp. 25. WAS DIRECTIONAL SURVEY MADE N

26. TYPE ELECTRIC AND OTHER LOGS RUN
Micro Log, Temp. Log, HRI Log, Den.-Neu. Log, GR-CBL-CCL 27. WAS WELL CORED N

28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8	36	237	12 1/4	141 cu. ft., Cir.	
7	20	3477	8 3/4	1333 cu. ft., Cir.	
4 1/2	11.6	8092	6 1/4	731 cu. ft., TOC 2250'	

29. LINER RECORD				30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)
					2 3/8	7937'

31. PERFORATION RECORD (Interval, size and number)		32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
DK-7929-37, 7343-45, 7978-83, 7997-8010 1JSPF (32 Holes) MV-5641, 45, 49, 57, 61, 63, 67, 69, 89, 91, 97, 99, 5708, 10, 12 14, 16, 18, 43, 57, 59, 68, 93, 98, 5805, 14, 5914, 18 1JSPF (28 Holes)		DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
		7929-8010'	37,000 Gals., Delta 200, 70,000# 20/40 Sand.
		5641-5918'	95,200 Gals., Slickwater, 110,000# 20/40 Sand. (See Back)

33.* PRODUCTION
DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump) Flowing WELL STATUS (Producing or shut-in) SI

DATE OF TEST 10/13/98 HOURS TESTED 7 Days SI CHOKE SIZE - PROD'N. FOR TEST PERIOD OIL - BBL. GAS - MCF. WATER - BBL. GAS - OIL RATIO
FLOW. TUBING PRESS. SI-1160# CASING PRESSURE SI-1160# CALCULATED 24-HOUR RATE Pitot Tube MV-3221 0 ACCE OIL GRAVITY - API (CORR.) RD

34. DISPOSITION OF GAS (Solid, used for fuel, vented, etc.) To Be Sold PC-537 TEST WITNESSED BY Perry Kirk

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records
SIGNED Monica Taylor TITLE Production Assistant DATE 10/14/98

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TRUE VERT. DEPTH
38.			31. MV-5128, 57, 92, 5209, 54, 5310, 5320, 60, 85, 5409, 30, 39, 5455, 56, 57, 78, 79, 93, 97, 99, 5504	Ojo Alamo	2360	
			05, 06, 26, 27, 29, 39, 42, 44, 47, 1JSPF (30 Holes)	Kirtland	2565	
			MV-4396, 4415, 47, 67, 72, 74, 83, 4501, 07, 4663, 79, 84, 88, 4715, 36, 79, 81, 4803, 24, 26, 48, 95, 4903, 4925, 4949 1JSPF (25 Holes)	Fruitland	2923	
				Pictured Cliffs	3170	
				Lewis	3223	
				Huerfanito Bent.	4202	
				Chacra	Not Present	
			32. 5128-5547' 72,000 Gal's., Slickwater.	Cliff House	5100	
			80,000# 20/40 Sand.	Menefee	5450	
			4396-4949' 76,250 Gal's., 60 Q Foam, 150,000# 20/40 Sand.	Point Lookout	5640	
				Mancos	6130	
				Gallup	6740	
				Greenhorn	7737	
				Dakota	7923	