

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-081181

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
San Juan 32-5 Unit

8. Well Name and No.
San Juan 32-5 Unit 14M

9. API Well No.
30-039-25896

10. Field and Pool, or exploratory Area
Blanco Mesa Verde/Basin
Dakota

11. County or Parish, State
Rio Arriba NM

SUBMIT IN TRIPLICATE

RECEIVED
AUG 3 1998

OIL CON. DIV.
DIST. 3

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

Taurus Exploration, U.S.A., Inc.

3. Address and Telephone No.

2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

828' FSL, 795' FEL, Section 26, T32N, R6W, NMPM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent
 Subsequent Report
 Final Abandonment Notice

TYPE OF ACTION

- Abandonment
 Recompletion
 Plugging Back
 Casing Repair
 Altering Casing
 Other Casing
- Change of Plans
 New Construction
 Non-Routine Fracturing
 Water Shut-Off
 Conversion to Injection
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/18/98 Ran 5 jts. 9 5/8", 36#, J-55, ST&C casing 222' set at 237'. Cemented with 150 sks. Class B w/ 2% CACL2 and 1/4# Flocele (177 Cu. FT.). Circ. 15 bls to surface. Plug down 2 a.m. 7/19/98. WOC 12 hrs. Tested casing to 600 PSI - Ok.

7/23/98 Ran 78 jts. 7", 20#, K-55, ST&C casing 3422; set at 3435'. Cemented with 590 sks. 65/35 Poz with 6% gel, 2% CACL2, 1/2#/sk flocele and 10#/sk gilsonite followed by 125 sks 50/50 Poz with 2% gel 1/2#/sk flocele and 10#/sk gilsonite and 2% CACL2 (1318 cu. ft.). Circ. 35 bbl to surface. Plug down 11 a.m. 7/23/98. WOC 12 hrs. Tested casing to 1200 psi - Ok.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Production Superintendent Date 7/27/98

(This space for Federal or State office use)

Approved by _____ Title _____
Conditions of approval, if any: _____

ACCEPTED FOR RECORD

JUL 30 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE
BY [Signature]