Form 3160-5 (June 1990)

or representations as to any matter within its jurisdiction.

UNITED STATES DEPARTMENT OF THE INTERIOR BURGALLOE LAND MANAGEMENT

FORM APPROVED

Budget Bareau No. 1004-01

Budget Bareau No. 1004-0135

DEPARTMENT OF THE INTERIOR		Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT		5. Lease Designation and Serial Mo.
201211		NM 29342
SUNDRY NOTICES AN	8. If Indian, Allottee or Tribe Name	
Do not use this form for proposa	Is to drill or deepen or reentry to a different reservoir.	
Use "APPLICATION FOR PE	RMIT" for such proposals	
SUBMIT IN TRIPLIC	CATE	7. If Unit or GA, Agreement Designation
. Type of Well		
Oil Ges	13 14 15 16 7 PM	
☐ Well ☐ Other	0/2	8. Well Name and No.
2. Name of Operator		CARRACAS 26 A #4
VASTAR RESOURCES, INC.	S 250 2000	9. API Well No.
3. Address and Telephone No.	(c) DEC	30-039-26307
1816 E. MOJAVE ST., FARMINGTON, NM	■ The proof of	10. Field and Pool, or Exploratory Area
1010 E. MUJATE ST., FARMINGTON, RM	07401 13031 330-4400	DAGIN FRUITIAND GOAL
1. Location of Well (Footage, Sec., T., R., M., or Survey Descript	ion)	BASIN FRUITLAND COAL
		11. County or Parish, State
1003' FNL, 778' FWL, Section 26, T32N, R	5W	
		RIO ARRIBA COUNTY, NM
12. CHECK APPROPRIATE BOX(a) TO INDICATE N	IATURE OF NOTICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION		
	Abandonment	Change of Plans
Notice of Intent	Recompletion	New Construction
	Plugging Back	Non-Routine Fracturing
Subsequent Report	Casing Repair	Water Shut-Off
	Altering Casing	Conversion to Injection
Final Abandonment Notice	Other DRILLING OPERATIONS	Dispose Water
		Plots: Report results of multiple completion on Well
j		Completion or Recompletion Report and Log form.)

7-30-00 Spud 12 1/4" hole @ 03:00. TD'd surface hole at 402' on 7-30-00 @ 10:00. Ran 9 joints 8 5/8" 24# J-55 STC casing to 401' and cemented with 300 sx Class B w/ 3% CaCl2 & 1/4 #/sx Flocel. Circulated 38 bbls cement to pit. Installed bradenhead & BOP. Tested BOP to 250 psi low 2000 psi high. Tested casing to 500 psi. Drilled out with 7 7/8" bit.

8-11-00 TD'd 7 7/8" hole at 3930' @ 00:00. Ran 95 joints 5 1/2" 17# K-55 LTC casing to 3930' and camented with 1000 sx 65/35 B/Poz w/ 6% gel, 5 #/sk Gilsonite & 1/4PPS Flocale followed by 100 sx 50/50 B/Poz w/ 2% gel 0.4% halad 344, 5 #/sk Gilsonite & 1/4PPS flocale. Circulated 10 bbls cament to pit. CIP 16:30 8-15-00. ND BOP, NU Wellhead, RD.

n: BLM, Farmington (Or + 3) N. Hell Well File	•	
14. I hereby certify that the foregoing is true and correct Signed Charles W. Kins Co.	۲۰ Tide_ Engineer 505 599 4308	ACOFATION FOR RECOR
This space for Fodoral or State office use)	Tide	DEC 0 7 2000
Conditions of approval, if any:		FAMILIANION DELL OFFICE BY
Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and v	willfully to make to any department or agency of the United States any false, fictitious or frame	Aufent statements

^{13.} Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*