Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** Lease Designation and Serial No. NM 59704 **SUNDRY NOTICES AND REPORTS ON WELLS** 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or deepen or reently to a different reservoir. Use "APPLICATION FOR PERMIT-" for such aroposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Gas **DEC 2000**] Well Well Other 8. Well Name and No. 2. Name of Operator RECEIVE Carraças 25 A #16 OILCON DIV **VASTAR RESOURCES, INC.** 9. API Well No. 3. Address and Telephone No. 30-039-26476 10. Field and Pool, or Exploratory Area 1816 E. MOJAVE ST., FARMINGTON, NM 87401 599-4300 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) BASIN FRUITLAND COAL 11. County or Parish, State 585' FSL, 710' FEL, Section 25, T32N, R5W RIO ARRIBA COUNTY, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Abandonment Change of Plans Notice of Intent Recompletion New Construction Plugging Back Non-Routine Fracturing \mathbf{x} Subsequent Report Casing Repair Water Shut-Off Altering Casing Conversion to Injection Final Abandonment Notice Other Dispose Water **Drilling Operations** (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-1-00 Spud 13 3/4" hole @ 18:30. TD'd surface hole at 1020' on 10-3-00 @ 06:00. Ran 22 joints 8 5/8" 24# K-55 STC casing to 1003 and cemented with 780 \$x Class H w/additives. Circulated 110 bbls cement to pit. Installed bradenhead & BOP. Tested BOP to 250 psi low 2000 psi high. Drilled out with 7 7/8" bit. 10-7-00 TD'd 7 7/8" hole at 3870' @ 16:00. Ran 94 joints 5 1/2" 17# K-55 LTC casing to 3850' and cemented with 914 sx Class H w/additives. Circulated 110 bbls cement to pit. CIP 19:25 10-11-00. ND BOP, NU Wellhead, RD. cc: BLM, Farmington (Or + 3) N. Hall Well File Title Engineer 915 683-8000 (This space for Federal or State office use)

FARMINGTON FIELD OFFICE Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or traudblest statements or representations as to any matter within its jurisdiction.