

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-039-26597
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-346
7. Lease Name or Unit Agreement Name: San Juan 32-5 Unit
8. Well No. 113
9. Pool name or Wildcat Basin Fruitland Coal
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6472' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-103) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other
2. Name of Operator ENERGEN RESOURCES CORPORATION
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401
4. Well Location Unit Letter <u>N</u> : <u>1070</u> feet from the <u>South</u> line and <u>1575</u> feet from the <u>West</u> line Section <u>32</u> Township <u>32N</u> Range <u>5W</u> NMPM County <u>Rio Arriba</u>
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6472' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: Set casubg ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Ran 72 jts. 7" 20# J-55 LT&C casing, set @ 3156'. RU Halliburton. Cement with 350 sks 65/35 Class B poz. 6%gel, 2% CaCl2, 10#/sk gilsonite, 1/4#/sk flocele followed with 100 sks 50/50 Class B poz. 2% gel, 1/4#/sk flocele, 2% CaCl2 (818 cu.ft.). Plug down @ 2:15 pm 10/06/01. Circulated trace of cement to surface. RD Halliburton. NU BOP. WOC. Test BOP & casing to 1800 psi - ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 10/11/01

Type or print name Vicki Donaghey Telephone No. 505-325-9732

(This space for State ORIGINAL SIGNED BY CHARLES T. PETERSON

APPROVED BY DEPUTY OIL & GAS INSPECTOR, DIST. 40 TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 40 DATE OCT 15 2001

Conditions of approval, if any: