



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 080657
Unit San Juan 32-5

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL, OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

OCT 17 1960

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 15, 1960

San Juan 32-5

Well No. 1-31 is located 990 ft. from N line and 713 ft. from E line of sec. 31

North 40 acres of
Section 31

(1/4 Sec. and Sec. No.)

32-North

(Twp.)

5-West

(Range)

N.M.P.M.

(Meridian)

Undesignated

(Field)

Rio Arriba County

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6,656 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On August 15, 1960, after drilling to 8369 feet - run 251 joints (8355') of 5-1/2" OD 17 1/2 N-80 casing. Run Baker two-stage collar at 8294'. Casing set at 8368'. Cemented first stage with 230 sacks 50/50 portland S with 2 1/2 gal and 4/10% of 1% MMA. On August 16th, opened stage collar - cemented with 230 sacks 50/50 portland S with 4 1/2 gal and 1 1/2% Gilsomite per sack. Moved rotary off.

On August 20, 1960, after rigging up cable tools, cleaned out to PWD of 8334'. Pressure tested casing at 3000# for 15 minutes. Spotted 1000 gallons 15% MMA with 6 gallons metal inhibitor. Run correlation log. Perforated 8295-8300, 8383-88, 8271-76, 8243-66, 8230-35, 8194-98, 8181-86' with 4 super dinajet shots per foot.

See report of sand water fracturing on separate report sheets.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company La Plata Gathering System, Inc.

Address Box 723

Farmington, New Mexico

C. Benson Neill, Agent in Farmington.

Title