

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
2. NAME OF OPERATOR  
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR  
P. O. Box 990, Farmington, N. M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FNL, 713' FEL, Sec. 31-32-5  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

SF 080657

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-5 Unit

8. FARM OR LEASE NAME

San Juan 32-5 Unit

9. WELL NO.

9

10. FIELD OR WILDCAT NAME

Blanco MV, and Basin DK

11. SEC., T., R., M., OR BLK. AND SURVEY OR

AREA Sec. 31, T32N, R5W NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6656' GL; 6666' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Tried to circulate MV side. Pressured up to 1000 psi. Pumped down DK tbg. (2 1/16") at 250 psi. Cemented DK zone through tbg. w/30 sx cement. Displaced tbg. Pulled 30,000 psi on MV (1 1/4") tbg. Shot tbg. off @3950'. (Tagged bottom @3962'). Pulled out 119 jts. 1 1/4". Latched on to DK tbg. and pulled 40,000 psi. Shot it off @5800' and pulled out 189 jts. (Could not get below 5800', tbg. seemed crimped). Ran back in hole w/2 1/16" tbg. to 5800' and cemented MV w/75 sxs. Cemented PC with 50 sx through perfs @3475' and Ojo Alamo with 50 sx through perfs @2510'. Tied in prod. csg. and surface csg. w/25 sx cement through perfs @800'. Spotted 10 sx plug at surface and installed dry hole marker. (Will clean up location and reseed when weather improves).

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jeff Perea

TITLE

Production  
Engineer

DATE

1-24-78



(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:



JAN 27 1978

U. S. GEOLOGICAL SURVEY  
BIRMINGHAM, ALA.