

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Indian Agency \_\_\_\_\_

Ute Mountain Tribal

Allottee \_\_\_\_\_

Lease No. 14-90-604-89

<b>X</b>			

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____	<u>JUL 28 1961</u>
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____	
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____	
NOTICE OF INTENTION TO ABANDON WELL _____		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Ute Mountain Tribal "A"

Farmington, New Mexico July 26, 1961

Well No. 2 is located 2125 ft. from [N] line and 660 ft. from [W] line of sec. 11

SW/4 NW/4 Section 11  
(1/4 Sec. and Sec. No.)

T-11N  
(Twp.)

R-15W  
(Range)

N.M.P.M.  
(Meridian)

Verde Valley  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 5575 ft. (OL)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

As a result of the above well ceasing to produce oil in commercial quantities we propose to plug and abandon it as follows:

1. Move in pulling unit and pull rods and tubing.
2. Re-run tubing with fishing tool to recover 1/2" liner (unaccounted) set 2504-2678 with perforations located 2566-2631 (details on liner above).
3. Spot 40 sacks cement plug on bottom (approximately) 150 feet of fill up to 2415 inside casing) & squeeze with minimum pressure to leave open hole covered with cement.
4. Fill hole with fluid.
5. Pump 25 sacks cement plug down 5-1/2" - 8-5/8" annulus (about 140' fill up).
6. Remove well head and surface equipment.
7. Spot 5 sacks cement plug for surface plug (0-40') and erect abandonment marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 480, Farmington, New Mexico

Attn: L. O. Spear, Jr.

ORIGINAL SIGNED BY  
R. M. Bauer, Jr./

By \_\_\_\_\_

Title Senior Petroleum Engineer