

(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R359.4
Approval expires 12-31-60.

Indian Agency Ute Mountain Tribal

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. 11-20-60-125

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

RECEIVED
JAN 19 1961
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Ute Mountain Tribal "R"

Farmington, New Mexico January 18, 1960

Well No. 2 is located 610 ft. from N line and 660 ft. from W line of sec. 35

W 1/4 of Section 35
(1/4 Sec. and Sec. No.)

T-11-N
(Twp.)

R-15-W
(Range)

N.M.P.M.
(Meridian)

Yorda Gallego
(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)



The elevation of the derrick floor above sea level is 5442 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

As a result of Ute Mountain Tribal "R" Well No. 2 ceasing to produce oil in commercial quantities, we propose to plug and abandon well as follows:

1. Move in pulling unit and pull rods and tubing.
2. Re-run tubing with fishing tool to recover 4" slotted liner set 3957-4111 (uncemented) with inverted Baker Texas Pattern Guide Shoe on top and Baker duplex shoe on bottom.
3. Spot 40 sacks cement plug on bottom (approximately 150' of fill-up inside casing to 3860) and squeeze with minimum pressure to leave open hole covered with cement.
4. Fill hole with fluid.
5. Pump 25 sacks cement down 5-1/2" - 8-5/8" annulus (about 145' fill).
6. Remove wellhead and surface equipment.

(See reverse side.)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 480

Farmington, New Mexico

Attn: L. O. Speer, Jr.

ORIGINAL SIGNED BY

R. M. Bauer, Jr.

By _____

Title Senior Petroleum Engineer

