Form 3160-5 (August 1999)	UNITED STA	IE INTERIOR	- AU22	OMB No.	NPPROVED - 1004-0135 ember 30, 2000
Do not use abandoned v	BUREAU OF LAND MA RY NOTICES AND RE this form for proposals well. Use Form 3160-3 (A	PORTS ON WELLS to drill or to re-ente APD) for such propos	Als. AUG 2001	14-20-604- 6. Hindian, Allottee	
SUBMIT IN T	RIPLICATE - Other ins	structions on rever	se side CON DIST.	7. If Cait or CA/Agre	ement, Name and/or No.
1. Type of Well	Other WATER INJ		(C)	HOUSE SHOE	GALLUP UNI
Name of Operator			- 68732	HGU #167	1.
VULCAN MINERALS 3a. Address HOUSTON, T 650 N.SAM HOUSTON P	X 77060 KWY.E.STE 500	3b. Phone No. (inclu	ide area code)	9. API Well No. 30-045-103 10. Field and Pool, or E	
4. Location of Well (Footage, Sec	c., T., R., M., or Survey Descript	tion)		HORSE SHOE	GALLUP UNIT
790' FSL, 3130' F SECTION 28, T-31N				11. County or Parish, S	late
	PPROPRIATE BOX(ES)	TO INDICATE NATI	IRE OF NOTICE	SAN JUAN,	NM _
TYPE OF SUBMISSION			YPE OF ACTION	CEPORT, OR OTHER	DATA
Notice of Intent KK Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction RY Plug and Abandon Plug Back	Production (Sta Reclamation Recomplete Temporarily Al Water Disposal	Well [Other bandon	Shut-Off Integrity
13. Describe Proposed or Complete If the proposal is to deepen dire Attach the Bond under which di following completion of the inv testing has been completed. Fi determined that the site is ready VULCAN MINERALS PR APPROVED ON 8-01-2	the work will be performed or proved operations. If the operational Abandonment Notices shall for final inspection.) LUGGED AND ABA	rovide the Bond No. on file on results in a multiple com be filed only after all requ	with BLM/BIA. Requipletion or recompletion irements, including recl	tier et subsequent reports shall in a new interval, a Form 3 amation, have been comple	tinent markers and zones. Il be filed within 30 days 3160-4 shall be filed once ted, and the operator has
SEE ATTACHED REPOR	RT FOR DETAILE	D INFORMATIO	N		
Ē					
1					
		•			,
14. I hereby certify that the foregoin	g is true and correct				· · · · · · · · · · · · · · · · · · ·
Name (Printed/Typed) NATHAN E. CRAWFORD	for Richard)	Pomrenke Title P.	&A SUPERVIS	SOR	
Signature Muthers (1)	Janden A		ULY 25, 200		
	THIS SPACE	FOR FEDERAL OR S			

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. **ACCEPTE** FOR RECORD Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

stu. Y	Swimmer	orric!
	Swin-	OFFIC

Date



Key Energy Services, Inc.

Four Corners Division 5651 US Highway 64 P.O. Box 900 Farmington, NM 87499

P&A OPERATION CEMENT SERVICE REPORT

Phone: 505-327-4935 Fax: 505-327-4962

WELL NAME: HORSE SHOE GALLUP UNIT #167

TOTAL PLUGS SET: 2

DATE STARTED: 07-23-01

TOTAL SACKS USED: 150 SX

DATE COMPLETED: 07-24-01

BLM WITNESS: M. GREY-LOPE OPERATOR WITNESS: N. WOODS

MOL AND SPOT RIG AND PLUGGING EQUIPMENT. RU RIG. BLED DOWN WELL, ND WELLHEAD AND RELEASE PACKER, WELL FLOWING AT 2 BBL/HR. NU BOP, TESTED BOP. POH AND STRAP OUT WITH 1556.46' OF 2 3/8" TBG AND LD PACKER.

PLUG #1 (PERFORATIONS, 1213' - 1608'), PU AND RIH WITH 5 ½" RETAINER AND SET AT 1494'. CIRCULATED CASING AND ATTEMPTED TO PRESSURE TEST TO 500 PSI, DID NOT TEST. ESTABLISHED INJECTION RATE INTO PERFORATIONS AT .5 BPM WITH 500 PSI. MIXED 58 SX CL. B CEMENT PLUG AND PLACED 33 SX BELOW AND 25 SX ONTOP OF RETAINER. POH AND WOC. RIH AND TAGGED TOC AT 1213'. POH.

PLUG #2 (SURFACE, SHOE, 0' - 308'), RU WIRELINE AND PERFORATED SQUEEZE HOLES AT 308'. POH. ESTABLISHED CIRCULATION TO SURFACE WITH 30 BBL WATER. MIXED 92 SX CL. G CEMENT PLUG TO CIRCULATE GOOD CEMENT TO SURFACE. RD FLOOR AND ND BOP. CUT OFF WELLHEAD AND INSTALLED DRY HOLE MARKER. RD RIG AND MOL.

NATHAN E. CRAWFORD. P&A SUPERVISOR