Forn (Ap	1 9-3 oril 19 <i>t</i>	31 b	\leq
		1	
X			

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR

	Agency	
Ute	Mountain	Tribal
Allotte	. 14-20-60	X88
į	No	

Budget Bureau No. 42-R359.4. Approval expires 12-31-60.

	GEOLOGICAL SURVE	Y Lease No.
		RECEIVED
SUNDRY N		ORTS ON WELLS T 14 1957
OTICE OF INTENTION TO DRILL	IS SUBSEQUENT R	REPORT OF WATER SHUT-OF MAINGTON, NEW MEX
OTICE OF INTENTION TO TEST WATER	3110 1-011 2-2-2-2	REPORT OF REDRILLING OR REPAIR.
OTICE OF INTENTION TO REDRILL OR		REPORT OF ABANDONMENT.
OTICE OF INTENTION TO SHOOT OR AC	1012222222	RY WELL HISTORY
OTICE OF INTENTION TO PULL OR ALTE	ER CIDITO	
OTICE OF INTENTION TO ABANDON WE		
(INDICATE A	BOVE BY CHECK MARK NATURE OF REPORT	
e Mountain Tribal "C"	Farmington	New Hexton October 11 , 19 57
	1.4.	1 550 (from 12) line of one 27
ell No is locat	ted 2260 ft. from $\{S\}$ line and	d 550 ft. from W line of sec. 27
	T-31-N R-15-W	H.W.P.W.
/4 of Section 27	(Twp.) (Range)	(Meridian)
(14 Sec. and Sec. No.)	San Juan	New Mexico
rde-Callup	(County or Subdivision)	(State or Territory)
(Field)		•
ne elevation of the derrick f	loor above sea level is 5666	ft.
	DETAILS OF WOR	
	objective sands; show sizes, weights, and let ing points, and all other important pr	ngths of proposed casings; indicate mudding jobs, cement- oposed work)
m September 16, 1957, 5 casing was perforated the contract that the contract the co	objective sands; show sizes, weights, and ler ing points, and all other important pr a cast iron bridge plug ted from 23881 to 24341	ngths of proposed casings; indicate mudding jobs, cement- oposed work) was set on wire line at 2436'. with four shots per foot. This gallens oil and 20,000 pounds sam are injection rate 64 barrels per
a September 16, 1957, 2 casing was perforated was then re-sand cornation broke at 2200 daute. Potential test	a cast iron bridge plug ted from 2388 to 2434 to 11 fracked with 20,000 pounds pressure. Aver to 10/10/57 91 barrels of must receive approval in writing by the Grand state of the control	ngths of proposed casings; indicate mudding jobs, cement- oposed work) was set on wire line at 2436'. with four shots per foot. This gallons oil and 20,000 pounds sam age injection rate 64 barrels per oil in 24 hours.
a September 16, 1957, 2 casing was perforated to the re-sand correction broke at 2200 daute. Potential test	a cast iron bridge plug ted from 2388 to 2434 to 11 fracked with 20,000 pounds pressure. Aver to 10/10/57 91 barrels of must receive approval in writing by the Grand state of the control	negligible of proposed casings; indicate mudding jobs, comentoposed work) was set on wire line at 2436'. with four shots per foot. This gallons oil and 20,000 pounds same injection rate 64 barrels per oil in 24 hours. Sological Survey before operations may be communiced.
a September 16, 1957, assing was perforated was then re-sand cornation broke at 2200 daute. Potential test transfer and the same and the same at the s	a cast iron bridge plug ted from 2388 to 2434 to 11 fracked with 20,000 pounds pressure. Aver to 10/10/57 91 barrels of must receive approval in writing by the Grand state of the control	ngths of proposed casings; indicate mudding jobs, cement- oposed work) was set on wire line at 2436'. with four shots per foot. This gallons oil and 20,000 pounds sam age injection rate 64 barrels per oil in 24 hours.
a September 16, 1957, 2* casing was perforated to the series of the series at 2200 daute. Potential test	objective sands; show sizes, weights, and let ing points, and all other important properties of the control of	negligible of proposed casings; indicate mudding jobs, comentoposed work) was set on wire line at 2436'. with four shots per foot. This gallons oil and 20,000 pounds same injection rate 64 barrels per oil in 24 hours. Sological Survey before operations may be communiced.