Form 3160-5 (August 1999)	UNITED STATES  DEPARTMENT OF THE INTERIOR  BUREAU OF LAND MANAGEMENT					FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000		
	SUNDRY NOTICES AND REPORTS ON WELLS					5. Lease Serial No. 14-20-604-1951		
	Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.  6. If Indian, Allottee or Tr							
	abandoned we	ell. Use Form 3160-3 (A	PD) for such p	roposais.		1		
<del> </del>	SUBMIT IN TR	IPLICATE - Other ins	tructions on	everse sic	ie	7. If Unit or Ca	A/Agreement, Name and/or No.	
I. Type of Well						HORSESH	OE GALLUP UNIT	
Oil Well Gas Well XXOther WATER INJECTION WELL						8. Well Name and No. HGU #160		
2. Name of Operator VULCAN-MINERALS & ENERGY dba REGENT ENERGY						9. API Well No.		
3a. Address H N.SAM H	1	3b. Phone No. (include area code) (281) 931-3800			30-045-10334  10. Field and Pool, or Exploratory Area			
		ŴY É.ŠŤĚ 500		<u> </u>	00	HORSESHOE GALLUP UNIT		
	NL, 1980'					11. County or P		
	28, T-31					SAN JUA	N, NEW MEXICO	
		PROPRIATE BOX(ES)	TO INDICATE	NATURE (	OF NOTICE, R	EPORT, OR O	THER DATA	
TYPE OF S	SUBMISSION			TYPE (	OF ACTION			
☐ Notice of	Intent	Acidize Alter Casing	Deepen Fracture To	_	Production (Star Reclamation Recomplete	t/Resume)	Water Shut-Off Well Integrity Other	
XX Subseque	nt Report	Casing Repair Change Plans	XX Plug and A	_	Temporarily At	_	Other	
Final Aba	indonment Notice	Convert to Injection	Plug Back		Water Disposal			
If the propo Attach the l following o testing has determined	isal is to deepen direct Bond under which the completion of the invi- been completed. Fir that the site is ready	ctionally or recomplete horizor he work will be performed or p olved operations. If the operat nat Abandonment Notices shal	ntally, give subsurta provide the Bond N tion results in a mu Il be filed only afte	ice locations and of on file with the liple completion all requirements.	nd measured and the BLM/BIA. Required on or recompletion substituting rections.	ue vertical depins of ired subsequent rep in a new interval, a amation, have been	and approximate duration thereof fall pertinent markers and zones onts shall be filed within 30 day form 3160-4 shall be filed one completed, and the operator ha	
	ED ON 8-01						_	
		PORT FOR DETAI	LED INFO	MATTON	J	ASS INC.		
_	m M		1111	14111101	 E	Alico	004	
	C						00 <b>1</b> (3)	
					(	Categy	One of	
:					<b>)</b>	Sect.		
					/	V		
	• •							
14. I hereby ce Name (Prin	tify that the foregoin	ng is true and correct						
		C	A A CONTRACTOR	Tisl-				
	CRAWFORD	for RICHARD F	OMRENKE	Title I	P&A SUPE	RVISOR		

Date Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. ACCEPTE FOR RECORL Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

SN- Urfice



Key Energy Services, Inc.

Four Corners Division 5651 US Highway 64 P.O. Box 900 Farmington, NM 87499

## P&A OPERATION CEMENT SERVICE REPORT

Phone: 505-327-4935 Fax: 505-327-4962

WELL NAME: HORSE SHOE GALLUP UNIT #160

**TOTAL PLUGS SET: 2** 

DATE STARTED: 07-24-01

**TOTAL SACKS USED: 180 SX** 

**DATE COMPLETED: 07-26-01** 

BLM WITNESS: M. GREY-LOPE OPERATOR WITNESS: N. WOODS

MOL AND SPOT RIG AND PLUGGING EQUIPMENT. RU RIG. BLED DOWN WELL, ND WELLHEAD AND RELEASE PACKER. NU BOP, TESTED BOP. POH AND STRAP OUT WITH 1571.06' OF 2 3/8" TBG AND LD PACKER.

PLUG #1 (PERFORATIONS, 1297' - 1628'), PU AND RIH WITH 5 ½" RETAINER AND SET AT 1515'. CIRCULATED CASING AND PRESSURE TESTED TO 500 PSI, TESTED GOOD. ESTABLISHED INJECTION RATE INTO PERFORATIONS AT 1 BPM WITH 1000 PSI. MIXED 58 SX CL. B CEMENT PLUG AND PLACED 33 SX BELOW AND 25 SX ON TOP OF RETAINER. POH.

PLUG #2 (SURFACE, SHOE, 0' – 334'), RU WIRELINE AND PERFORATED SQUEEZE HOLES AT 334'. POH. ESTABLISHED CIRCULATION TO SURFACE WITH 30 BBL WATER. MIXED 122 SX CL. G CEMENT PLUG TO CIRCULATE GOOD CEMENT TO SURFACE. RD FLOOR AND ND BOP. CUT OFF WELLHEAD AND INSTALLED DRY HOLE MARKER. RD RIG AND MOL.

NATHAN E. CRAWFORD. P&A SUPERVISOR