

WORKOVER

12-22-62 Young Drilling Company rigged up.
 12-26-62 Pulled tubing. Running log.
 12-28-62 Set Baker Model "K" Magnesium Bridge Plug @ 4504'. Tested casing to 3000#.
 12-29-62 Cleaning out open hole.
 12-31-62 Ran 14 joints of 4 1/2" 10.5# J-55 liner (446') set from 4422' to 4872'.
 Cemented w/200 sacks 50-50 Litepoz & Class "C" cement, 1/4 cu. ft.
 Strata-Crete "6"/sk.
 1-1-63 B & R temperature survey @ 4420'. Set RTTS packer @ 4389'. Squeezed
 perf @ 4590' w/100 sacks regular, 2% calcium chloride
 Perf 4766-72, 4710-16, 4689-95 (2 SPF); 4610-22 (1 SPF); 4586-92 (2 SPF);
 frac w/62,050 gallons water, 60,000# sand. Flush w/8400 gallons water.
 IR 61.5 BPM. Max pr 1900#, BDP 1200#, tr pr 1600-1350-1500-1600-1900#.
 4 drops of 12 balls.
 1-5-63 Ran 17 1/4 joints 2 3/8" 4.7# tubing (4826') set at 4836'. Shut in for test.
 1-16-63 Date well was tested.

WORKOVER

12-22-62 Young Drilling Company rigged up.
12-26-62 Pulled tubing. Running log.
12-28-62 Set Baker Model "K" Magnesium Bridge Plug @ 4504'. Tested casing to 3000#.
12-29-62 Cleaning out open hole.
12-31-62 Ran 14 joints of 4 1/2" 10.5# J-55 liner (446') set from 4422' to 4872'.
Cemented w/200 sacks 50-50 Litepoz & Class "C" cement, 1/4 cu. ft.
Strata-Crete "6"/sk.
1-1-63 B & R temperature survey @ 4420'. Set RTTS packer @ 4389'. Squeezed
perf @ 4590' w/100 sacks regular, 2% calcium chloride
Perf 4766-72, 4710-16, 4689-95 (2 SPF); 4610-22 (1 SPF); 4586-92 (2 SPF);
Frac w/62,050 gallons water, 60,000# sand. Flush w/8400 gallons water.
IR 61.5 BPM. Max pr 1900#, BDP 1200#, tr pr 1600-1350-1500-1600-1900#.
4 drops of 12 balls.
1-5-63 Ran 17 1/4 joints 2 3/8" 4.7# tubing (4826') set at 4836'. Shut in for test.
1-16-63 Date well was tested.