


REVISED
(SUBMIT IN TRIPLICATE)Indian Agency **Consolidated Ute**
Agency, Ignacio, Colorado
Allottee **Ute Mountain Tribe**
Lease No. **14-20-604-119**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	XX	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 14

19 58

Pueblo Mountain
Well No. **Ute #19-16** is located **660** ft. from **S** line and **679** ft. from **E** line of sec. **19**
Sec. 19 (1/4 Sec. and Sec. No.) **31 North 14 West N.M.P.M.** (Twp.) (Range) (Meridian)
Verde-Gallup **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the **ground level** ~~anticline~~ above sea level is **5277** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

It is proposed to drill with rotary tools to a depth of 100+ feet, set 8-5/8" casing and cement to surface with 100 sax. Thereafter to drill with rotary to the top of the fractured Gallup producing zone, estimated at 3270' +, run electric log and run 5-1/2" casing with a 2-stage BV cementing tool. It is proposed to cement the first stage with 50 sax and to cement the second stage with 50 sax to be followed by a temperature survey in order to determine cement fill-up. It is proposed to place the BV tool approximately 100 feet below the base of the Point Lookout formation. After waiting a minimum of 24 hours on cement, it is proposed to drill in with rotary using oil as drilling fluid and then free through casing with 42,000 gallons of crude and then run tubing and place on pump until daily rate of production is established after re-covering free oil. The ~~SW 1/4~~ ^{SE 1/4} of the section, containing 49 acres more or less, is dedicated to the well site. Estimated total depth, 3,390 feet.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **FURCO PETROLEUM CORPORATION**Address **P.O. Box 1419****Albuquerque, New Mexico**By
Frank D. Graham, Jr.
Title **Vice President**