Revised 12-1-55

MULTI-POINT	BACK	PRESSURE	TEST	FOR	GAS	WELLS
-------------	------	----------	------	-----	-----	-------

Pool		00		_For	mation_				_County	_Ann)	
Init	ial 🗶		Annual_			Spec	ial		_Date of	Test	44/4	
Compa	any Actor	<u>en v e</u>	to Comp	-	I	_ease			Wel	1 No		
Unit	S	ec	_Twp	22	Rge	. 10	Purcl	naser				
Casin	ng 7° W	t. 😰 🌡	L.D.	6,1	Set	at_	Pei	rf		То		
												30
	icing Thru:											
Date	of Complet	ion•	O <u></u>		Packer	. 9866	Sing	gle-Brade Reservo	nhead-G.	G. or (3.0.	Dual
Dave	OI COMPICO			 ~			ED DATA					
		(5) (a))	\ \	Sec. 1		ED DATA		M Ma	_		
Teste	ed Through								Type Tap			
	(Prover)		ow Data			Temp	Tubing		Casing D		1	Duration
No.	(Line)	(Orifi	ce)		J				psig	Į.	1	of Flow
7	Size			sig	h _w	°F.	ps1g		psig	· ·	 	Hr.
SI		0,73	<u> </u>	-+				60	7.5	 	 	7 Augusta
1. 2. 3.												
3.		-								ļ	 	
4. 5.	,,,									 	 	
						7 01 04 7	OUT A MITON		·			
	Coeffici	ent		Pre		El our	CULATION:	Charritar	Compre	ss.	Rate	of Flow
No.	(24-Hou	l l				Fac	tor	Factor	Facto	r	Q-M	CFPD .025 psia
		r) \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	/ n _w p _f	4	sia	F.	t	rg	p v		W 1)	•02) psia
1. 2. 3. 4. 5.	12,365				13			0.9600	1.0	0		
3.												
4.				+								
_2:												<u> </u>
					PRI	ESSURE C	ALCU ATI	ONS				
	iquid Hydro					cf/bbl.			fic Gravi			
	ty of Liqui			-81		deg.			fic Gravi	ty Flor p2		Fluid
ГС			(e				•	, c		c		
	D											
No.	$P_{\mathbf{w}}$	$P_{\mathbf{t}}^2$	F _c Q		$(F_cQ)^2$	(F	cQ) ² -e-s)	P_w^2	$P_c^2 - P_w^2$		al.	Pw Pc
	Pt (psia)					(1	_e-s)]	P _w	Pc
1.	793			-				Brown	70.75	+		
3.				_								
1. 2. 3. 4.			Ţ							 		
									<u> </u>			
	lute Potent	ial:		12_		MCFPD;	n a	15				
COMP.	ANY ESS									- -		
AGEN'	T and TITLE	ORIGIN	AL SIGNED	BY L	M. STEVE	INS		to the	Hi, Ma			
	ESSED	10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1										
COMP	ANY					REM	ARKS					
	4	*										

RECEIVED TOOM.

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- $P_{\mathbf{w}}^{-}$ Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{W}}^{\perp}$ Differential meter pressure, inches water.
- F_g : Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

STATE OF NEV	N MEXICO
OIL CONSERVATION	COMMISSION
AZT. C. DISTRI	CT OFFICE
NUMBER OF COP ES RECEI	vao 3
DiSTale	ON
SANTA FE	
FILE	
บ.ร.ด.ร.	
TALE OFFICE	
TALINGSONTED 1 T	il
PROJECTION OFFICE	
DOCUATOR	