F	OFI (A)	<b>n 9-</b> 8 pril 19	381 b 52)		
Γ					
ľ				-	
ľ					

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency ,
Window Rock
Allotte Navajo-Ute Itn. Tribe
Loss No. 11=20=600=3531

	SUNDRY N	OTICES A	ND REPORT	rs on well	S
	NTION TO DRILL		1		MAY 1 5 1969
	NTION TO CHANGE PLAN			T OF WATER SHUT-OFF	in OLOGICA
	NTION TO TEST WATER:			T OF ALTERING CASING M	
	NTION TO REDRILL OR		ii	T OF REDRILLING OR REPAI	1 1
TICE OF INTE	NTION TO SHOOT OR AC	DIZE		T OF ABANDONMENT	
TICE OF INTE	NTION TO PULL OR ALTI	ER CASING		LL HISTORY	*
	NTION TO ABANDON WE				
Nex	vaio B		NATURE OF REPORT, NOTICE	May 8	·
Nav	vajo B 11 is locat	ed <u>660</u> ft. fro	om S line and7	May 8	·
Nav Il No.	vajo B 11 is locat	ed <u>660</u> ft. fro		C3 ft. from W lin	·
Nav	vajo B  11 is locate  Sec. 19  nd Sec. No.)	ed 660 ft. fro	om S line and7	May 8	·
Nav Il No Svi (4 800. ar	Vajo B  Lis is locate  Sec. 19  nd Sec. No.)  (Jalling lield)	ed <u>660</u> ft. fro	om S line and 7	C3 ft. from W lin	e of sec. 19
Nav Il No Svi (4 8ec. ar	Vajo B  Lis locate  Sec. 19  Id Sec. No.)  (Jalling  Held)  ground	ed 660 ft. fro	om S line and 7	May 8  C3 ft. from W line  New Manager	e of sec. 19
Nav Il No. Sti (34 Sec. ar	Vajo B  Lis locate  Sec. 19  Id Sec. No.)  (Jalling  Held)  ground	ed 660 ft. fro	om S line and 7 (Range)  June 1  Grange or Subdivision)	May 8  O3 ft. from W lin  Man P. H.  (Meridian)	e of sec. 19

Spudded 4:00 P.11., 4-19-59. Brilled to 98' SUI. Ran 3 joints 8-5/8" J.D. 2h# 3-55 casing = 8h.45'. Set at 93.45' and comented with 90 sacks common cement plus 3% CaCl. Job complete 1:00 P.M., 4-21-59. WCC 3 days. Tested 8-5/8" casing with 500% for 30 minutes, 0.%. Brilled to 1467' TD. Ran Induction ES, their TD 1567'. Ran 48 joints 4-1/2" J.D. 9.5% J-55 casing = 1554.76'. Set at 1561.79' and cemented with 210 sacks Pozmix. Flug down 2:00 P.M., 4-26-59. WCC to 6:00 A.H., 4-28-59. Tested 4-1/2" casing with 1000% 30 minutes, 0.%. Ran Garma Ray Correlation log. Perforated 1506-1526' Schl. = 1505-1525' GR with 40 jets. Treated perforations with 20,000% 10/20 sand in 13,146 gallons lease crude. Formation broke down 1800-1400%. Average treating pressure 1500% at the rate of 33 BPM. Perforated 1391-1414' Schl. = 1390-1413' GR with 46 jets. Treated perforations with 20,000% 10/20 sand in 9,240 gallons lease grude. FBD 1700-1500%. Average treating pressure 1500% at the rate of 34 BPM. Job complete 1:00 P.M., 4-28-59. First fracture troated completed at 10:30 A.H., 4-28-59.

I understand	that this plan of work s	sust receive approval in writing b	by the Geological Survey before operations may be commenced.
Company	The Atlentic	Refining Company	
Address	P. 0. Box 520	# 1	
	Casper, Wyoni	<b>ng</b>	By addlope be
			Title Drilling Superintendent

47. 64.	€ %	PĀS				
OF.	<b>用製料</b>	EOY"		033	a ofsta	
	\$ 1 T	K.R	n gr	u se		關語
	SOLD OF		tions.	r i	palite :	ing kapatanii
		*	a.we		e The state of the	

e assind held from the 19-19. The that to 90' Bil. Rea 3 joints 8-5/6" Cal. Alf delighted and the light of the cases of the first and animals of the state. 0.00 Feb., helless, 700 3 days. Forted 9-5/0" cented with 500/ for 30 minutes, 0.5. helles so 7667 in, her industries is, thate to 1567. Ran is jointe hel/2" 0.5. 9-58 5-55 cented to Chilles Sed at 1501.00 rol emented with 210 and a Pozate. They down 2:00 Pully helded 3. at the control of the correct investing presence 3500% at the rate of 31 BM. Perforated 1571-1411/8 Schie = 1590with the little had become breaked partierations with 20,000/ 10/20 sould in Paile far house with the color of the first and constant with the color of the color 1907 Palla de 20-99. Prost frechure incided completed at 10:30 April 1928-99.

Transfer Herenton Democra

CONTRACTOR

क्रातिक्षण्डी व्यवसूक्तिः

BALLIAN PLANTEN PROBLEM PROBLEM