

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
W.M. Gallaway

3. ADDRESS OF OPERATOR
101-2 Petroleum Plaza Bldg. Farmington, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other)

SUBSEQUENT REPORT OF:

RECEIVED

AUG 19 1981

U.S. GEOLOGICAL SURVEY
DURANGO, COLO.

5. LEASE
14-20-604-1893

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
UTE MOUNTAIN INDIAN

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
UTE INDIAN D

9. WELL NO.
16

10. FIELD OR WILDCAT NAME
VERDE GALLUP

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 24, T31N, R15W

12. COUNTY OR PARISH
SAN JUAN

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DE, KDB, AND WD)
5574 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/5/81 Filled hole w/gel water, circulated w/45⁰ tubing sub.
Spotted 20 sks cement across Gallup perms. 2990'-2892'
and continue up 4" liner 50'

6/6/81 Tagged top of cement 2700' in 4" Liner
Spotted 20 sks cement across top of Point Lookout 1500'-1600'
Stretch 5½" csg, shot @ 1425' pulled csg.
Spotted 20 sks cement across 5½" stub 1475'-1375'
Spotted 20 sks cement bottom of surface csg. 50'

6/8/81 Spotted 10 sks in top of surface, and erect dry hole marker
and clean location.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert W. Brasher

TITLE

Agent

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

*See Instructions on Reverse Side

