

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other
2. NAME OF OPERATOR  
W.M. Gallaway
3. ADDRESS OF OPERATOR  
101-2 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL 660'/FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT OFF  
FRACTURE TRIAL  
SHOOT OR ACIDIZE  
REPAIR WELL  
PULL OR ALTER CASING  
MULTIPLE COMPLETE  
CHANGE ZONES  
ABANDON\*  
(other)

SUBSEQUENT REPORT OF:

RECEIVED

AUG 19 1981

U.S. GEOLOGICAL SURVEY  
DURANGO, COLO.

5. LEASE  
14-20-604-1893
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
UTE MOUNTAIN INDIAN
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
UTE INDIAN D
9. WELL NO.  
16
10. FIELD OR WILDCAT NAME  
VERDE GALLUP
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 24, T31N, R15W
12. COUNTY OR PARISH  
SAN JUAN
13. STATE  
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5574 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/5/81 Filled hole w/gel water, circulated w/45<sup>0</sup> tubing sub.  
Spotted 20 sks cement across Gallup perfs. 2990'-2892'  
and continue up 4" liner 50'

6/6/81 Tagged top of cement 2700' in 4" Liner  
Spotted 20 sks cement across top of Point Lookout 1500'-1600'  
Stretch 5½" csg, shot @ 1425' pulled csg.  
Spotted 20 sks cement across 5½" stub 1475'-1375'  
Spotted 20 sks cement bottom of surface csg. 50'

6/8/81 Spotted 10 sks in top of surface, and erect dry hole marker  
and clean location.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Robert W. Rasmussen*

TITLE

*Agent*

DATE

*8/14/81*

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

David J. Miller

TITLE

*Res Manager*

DATE

FEB 24 1984

\*See Instructions on Reverse Side

RECEIVED

FEB 28 1984

OIL CON. DIV.