

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

JUN 18 1992

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address and Telephone No.

221 Petroleum Center Bldg., Farmington, NM 87401 (505) 325-8874

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1984' FNL, 665' FWL, Section 22, Township 31N, Range 14W

5. Lease Designation and Serial No.

14-20-604-83

6. If Indian, Allottee or Tribe Name

Ute Mountain Tribal

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ute Mountain ~~14-20-604-83~~ #13

9. API Well No.

10. Field and Pool, or Exploratory Area

Verde Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cement plug #1 from 2831' to 2327'.

Cement plug #2 from 1475' to 1344' (calculated).

Surface cement plug from 170' (5-1/2" casing perforated at 170' by using Haliburton Wireline to run powder loaded cannister) to surface inside outside 5-1/2" casing.

9.5 #/gallon or heavier fresh gel mud pumped between cement plugs.

Operator will cut off casing below ground level - Weld a 1/4" steel plate across 8-5/8" casing - Erect P&A marker - Clean and restore surface.

Restoration and seeding requirements will be completed when program is received from Bureau of Land Management or Ute Mountain Tribal Indian Agency.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Virgil L. Stoabs
Vice-President

Date

6-12-92

(This space for Federal or State office use)

Approved by

Title

ACTING AREA MANAGER

Date

JUN 19 1992

Conditions of approval, if any:

Benson-Montin-Greer Drilling Corp.
Ute Mountain Tribal 83 No. 13
SW NW Sec. 22, T. 31 N., R. 14 W.
San Juan County, New Mexico

Conditions of Approval

1. This Subsequent Report of Abandonment (SRA) is approved for the plugging of the well bore only. Liability under the bond is retained until surface restoration is completed and approved.
2. Once surface reclamation has been completed, the operator will submit Form 3160-5 (Sundry Notice), informing the Bureau of Land Management (BLM) of this operation. This Sundry Notice or Second Subsequent Report of Abandonment (SSRA) will be an acceptance rather than an approval action. (Instruction Memorandum No. CO-87-417).
3. Form 3160-5, Sundry Notice, will be submitted when all restoration is completed. This Sundry Notice, or Final Abandonment Notice (FAN) will be submitted only when the site is ready for inspection by an official of the BLM and/or BIA.