STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

OIL COM DIV.

This form is not to be used for reporting packer leakage tests

	AN	10CO PRODUCT	ION COMPANY ARMINGTON, N		Mudge	B 1	Vell 10. <u>13</u>
ition Vell: Uni	ı G	_Sec. <u>20</u> T	wp. 3 (N	Rge	I W	County _	SAN JUAN
	NAME OF RESERVOIR OR POOL			TYPE OF PR	-	THOD OF PROD. Flow or Art. UII)	PROD, MEDIUM (Tbg. or Cag.)
per Blanco MV			GAS		FLOW.	TBG	
Dianco III			GAS		FLOW	TBG	
	Da	sin DK	PRE-FLO	W SHUT-IN P	RESSURE DATA		
	Hour, date shut-in Langth of time shut-in 72 HOUR.			in RS	SI press paig	Stabilized? (Yes or No)	
pietion 11 / 10 / 1999 Hour, date shut-in [1 / 16 / 1999		Langth of time shut-	Length of time shut-in 72 HOURS		51 Stabil	tzed? (Yes or No) YES	
				FLOW TEST	NO. 1 Zone producing (Up		
menced at		LAPSED TIME	PRESS Upper Completion	BURE	PROD. ZONE TEMP.		REMARKS
(hour. da		Day 1	185	200		BOTH ZONES	SHUT IN
/17 /		Day 2				BOTH ZONES	SHUT IN
			228	200		BOTH ZONES	SHUT IN
/ 18/		Day 3	242	200		FLOW Upp	er ZONE
/19 /		Day 4	195	280		11 1	1 11
1901	-	Day 5	148	200		11	1 11
<u>/21/</u>		Day 6	138	Taken b	y Terry Nee	<u> </u>	
il:		luring test	PD based on	Bbls.		15 G12	v GOR
as:			•		PRESSURE DAT		
Upper	Hour, date	anut-in	- Length of time a		SI press. psig		apilized? (Yes or No)
Lower Hour, date shut-in Length of time an				nutin	SI gress, paig Stabi		abilized? (Yes or No)

FLOW TEST NO. 2

TIME	LAPSED TIME	ME PRESSURE		Zone gradualing (Upper or Lawert		
(hour, date)	SINCE * #	Upper Completion	Lower Completion	PROD, ZONE TEMP.		
				AMP.	REMARKS	
	 					
				- Table - no.		
uction rate di						
uks:				ornice of Weter)	Grav GOR	
	the case of the same of the sa					
by certify tha	it the information	herein container	is true and com-	-1		
					of my knowledge.	
w Mexico Oil OPIGINAL S	Conservation Div	sion	19 Ope	Amo c	of my knowledge. O Production Company o Bradshaw	
w Mexico Oil OPIGINAL S	Conservation Div	ision	19 Ope	Sher	o Production Company	
w Mexico Oil OPIGINAL S	Conservation Div	ision	19 Ope By Tide	Sher	o Production Company	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tens shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packet or the tubing have been disturbed. Terts shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset
- 3. The packer leakage test shall commence when both zones of the dual completion are shur-in for pressure stabilization. Both zones shall remain shur-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such text shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three nours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accor-
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at firteen-minute intervals during the first hour thereof, and at bourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).