

RECEIVED

JUL 17 1992

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTBureau of Land Management
Durango, ColoradoFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil
☒ Well ☐ Gas Well ☐ Other

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address and Telephone No.

221 Petroleum Center Bldg., Farmington, NM 87401 (505) 325-8874

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

639' FNL, 500' FEL, Section 21, T31N, R14W

5. Lease Designation and Serial No.

14-20-604-83

6. If Indian, Allottee or Tribe Name

Ute Mountain Tribal

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ute Mountain Tribal #11

9. API Well No.

10. Field and Pool, or Exploratory Area

Verde Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Cement plug #1 from 2757' to 2423'.

Cement plug #2 from 1430' to 1282' (Calculated).

Surface cement plug from 155' (5-1/2" casing perforated at 155' by Basin Perforators) to surface inside and outside 5-1/2" casing.

9.5 #/gallon or heavier fresh gel mud pumped between cement plugs.

Operator will cut off casing below ground level - Weld a 1/4" steel plate across 8-5/8" casing - Erect P&A marker - Clean and restore surface.

Restoration and seeding requirements will be completed when program is received from Bureau of Land Management or Ute Mountain Tribal Indian Agency.

14. I hereby certify that the foregoing is true and correct

Signed *Virgil L. Stoabs*

Title Vice-President

Date July 13, 1992

(This space for Federal or State office use)

Approved by *(S) Karl Hoffman*

Title AREA MANAGER

Date JUL 21 1992

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NM500

RECEIVED
BLM

92 JUL 14 AM 11:33

019 FARMINGTON, N.M.

COPIED TO BLM

Benson-Montin-Greer Drilling Corp.
Ute Mountain Tribal 83 No. 11
NE NE Sec. 22, T. 31 N., R. 14 W.
San Juan County, New Mexico

Conditions of Approval

1. This Subsequent Report of Abandonment (SRA) is approved for the plugging of the well bore only. Liability under the bond is retained until surface restoration is completed and approved.
2. Once surface reclamation has been completed, the operator will submit Form 3160-5 (Sundry Notice), informing the Bureau of Land Management (BLM) of this operation. This Sundry Notice or Second Subsequent Report of Abandonment (SSRA) will be an acceptance rather than an approval action. (Instruction Memorandum No. CO-87-417).
3. Form 3160-5, Sundry Notice, will be submitted when all restoration is completed. This Sundry Notice, or Final Abandonment Notice (FAN) will be submitted only when the site is ready for inspection by an official of the BLM and/or BIA.