

RECEIVED

MAY 29 1992

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTBureau of Land Management
Durango, Colorado

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such purposes.

SUBMIT IN TRIPLICATE

AUG 27 1998

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address and Telephone No.

221 Petroleum Center Bldg., Farmington, NM 87401 (505) 925-8874

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL, 660' FBL, Section 21, T31N, R14W, NMPM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Well Name Designation and Serial No.

14-20-604-83

6. If Indian, Allottee or Tribe Name

Ute Mountain Tribal

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ute Mountain Tribal #8

9. API Well No.

30-045-10619

10. Name and Pool, or Exploratory Area

Verde Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other

- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Shooting Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completions on Well Completion or Resumption Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and areas pertinent to this work.)

Cement plug #1 from 2893' to 2300'.

Cement plug #2 from 1600' to 1407'.

Surface cement plug from 170' (4" and 5-1/2" casing perforated at 170' by Basin Perforators) to surface inside and outside 5-1/2" casing.

9.5 #/gallon or heavier fresh gel mud pumped between cement plugs.

Operator will cut off casing below ground level - Weld a 1/4" steel plate across 8-5/8" casing - Erect P&A marker - Clean and restore surface.

Restoration and seeding requirements will be completed when program is received from Bureau of Land Management or Ute Mountain Tribal Indian Agency.

SEE ATTACHED
CONDITIONS OF SALE

14. I hereby certify that the foregoing is true and correct

Signed

Virgil L. Stoabs
Vice-President

(This space for Federal or State office use)

JUNE 5-22-92

Approved by

(s) Kent Hoffman

Title

ACTING AREA MANAGER

Date

JUN 4 1992

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

DURANGO OFFICE COPY